


**ROY 2 (RY-80091)****Product description**

4 Busbar 3 Circuit

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 90°, Rotation 355°
- Proprietary lens design for high LOR
- Integral control gear
- Universal adaptor compatible with any track

**Optic**

N M W

**Product colour**

08 - Glossy White (RAL 9010) 09 - Glossy Black (HB451022M)

**ROY 2 (RY-80091)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	7 LED
<b>Power</b>	12 W
<b>Lumen</b>	878 - 1024 lm
<b>Efficacy</b>	73 - 85 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)

<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	15°, 27°, 35°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off
<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	0.6 kg

<b>Operating temperature</b>	-20 °C to 40 °C
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 120,000
<b>Lifetime L80B10 (hours)</b>	> 120,000
<b>Lifetime L80B50 (hours)</b>	> 120,000
<b>Variants (On/Off)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

RY-80091

