



KIOS 2 (KI-60465)**Product description**

With recessing box / driver - Embross frame

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- 5.5 mm thick front ring in grade 316 stainless steel
- Single cable entry, through wiring upon request
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear or frosted toughened glass
- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the luminaire and the illuminated surface should be at least 0.5 m

Optic

C F

Product colour

00 - Stainless Steel

KIOS 2 (KI-60465)


Technical information

Material	Stainless Steel
Light source	12 LED
Power	6 W
Lumen	85 - 317 lm
Efficacy	14 - 53 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	C, F

Optic value	98°, 75°
CCT / CRI	2700K CRI80, 3000K CRI80, 4000K CRI80
Bug	B0-U3-G0
ULR	100%
ULOR	100%
Dimming type	On/Off, 1-10V, DALI
Product colours	Stainless Steel
Weight	5.2 kg
Operating temperature	-20 °C to 40 °C

Through wiring	Single cable entry, through wiring upon request
Lens / Reflector / Optic	Clear or frosted toughened glass
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 23,000
Lifetime L80B10 (hours)	> 45,000
Lifetime L80B50 (hours)	> 50,000
Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

KI-60465




KIOS 2 (KI-60465)**Accessory**

Anti slip glass
A61512



Connector IP68 3 Pin Power
A62591



Honeycomb louvre
A62021



DALI Control System
Control-DALI



Connector IP68 5 Pin Power +
Signal
A613191

Please contact the factory for technical details if you wish to use Anti-glare accessories, Colour filters, Lenses and slip glasses in combination.