

NYBRO 4 (NYB-80355)



Product description

Down - 60x80 mm - 2330 mm - Trimless - Tunable White




microPrim™

Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Stainless steel brackets and screws for mounting
- Down light distribution only
- Wireless control available through Bluetooth connection
- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



Special finishes upon request




NYBRO 4 (NYB-80355)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	MacAdam Ellipse	3 SDCM
Light source	288 LED	Optic	O, P	Lifetime L90B10 (hours)	> 23,000
Power	74 W	CCT / CRI	TW (2700K - 6500K)	Lifetime L80B10 (hours)	> 45,000
Lumen	6323 lm	Dimming type	DALI	Lifetime L80B50 (hours)	> 50,000
Efficacy	75 lm/W	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver option	Integral control gear				
Driver	Constant current (CC)				
		Weight	7.3 kg		
		Operating temperature	-20 °C to 40 °C		

NYB-80355



NYBRO 4 (NYB-80355)**Accessory**



Continuous-coupler bracket
(60/70 mm Down & 60 mm
Down & Up profile)
A81581



Wireless bluetooth converter
A90291



Xpress wireless switch
A90591
