


**GAVLE 1** (GAV-80062)



**Product description**

Down - 70x90 mm - 4000 mm - Tunable White




microPrim™

**Luminaire Structure**

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA diffuser (UGR <19) for glare control
- Integral control gear
- Stainless steel brackets and screws for mounting
- Wireless control available through Bluetooth connection
- Daylight and occupancy sensor options
- Down light distribution only

**Optic**



0

**Product colour**



01 - Black (RAL 9011)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban



SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**GAVLE 1 (GAV-80062)**


**Technical information**

|                      |                       |
|----------------------|-----------------------|
| <b>Material</b>      | Aluminium             |
| <b>Light source</b>  | 3072 LED              |
| <b>Power</b>         | 206 W                 |
| <b>Lumen</b>         | 21072 lm              |
| <b>Efficacy</b>      | 102 lm/W              |
| <b>Driver option</b> | Integral control gear |

|                      |                       |
|----------------------|-----------------------|
| <b>Driver</b>        | Constant current (CC) |
| <b>Input voltage</b> | 220-240 V 50/60 Hz    |
| <b>Optic</b>         | 0                     |
| <b>Optic value</b>   | 102°                  |
| <b>CCT / CRI</b>     | TW (2700K - 6500K)    |
| <b>Dimming type</b>  | DALI                  |

|                              |   |
|------------------------------|---|
| <b>Product colours</b>       | Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland |
| <b>Weight</b>                | 27.2 kg   |
| <b>Operating temperature</b> | -20 °C to 40 °C   |
| <b>Variants (DALI)</b>       | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)                                   |

GAV-80062



**GAVLE 1 (GAV-80062)**

**Accessory**

---



---

Xpress wireless switch  
**A90591**

---



---

Wireless bluetooth converter  
**A90291**

---



---

DALI Control System  
**Control-DALI**

---