


PERTH 2 (PER-80002)**Product description**

Without remote driver - Constant current (CC) 260 mA
- Ø66 mm - 70 mm - 9 W LED Module

**Luminaire Structure**

- Lamp modules with different trim options
- Trim is a required accessory, please choose one
- Trims are White (03- RAL9003) as standard, Black is (01-RAL9011) upon request
- Remote driver (not included)
- Standard: 3000K (2700K and 4000K available upon request)

Optic**Product colour**

00 - Stainless Steel

PERTH 2 (PER-80002)


Technical information

Material	Stainless Steel
Light source	1 COB
Power	9 W
Lumen	787 - 943 lm
Efficacy	87 - 105 lm/W
Driver option	Remote driver (not included)

Driver	Constant current (CC)
Input voltage	260 mA, 23-46 VDC
Optic	C, F
Optic value	53°, 59°
CCT / CRI	3000K CRI90
Dimming type	On/Off, 1-10V, DALI

Product colours	Stainless Steel
Weight	0.1 kg
Operating temperature	-20 °C to 40 °C
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

PER-80002



PERTH 2 (PER-80002)**Accessory**

Trim - Deep recessed (White)
A80001-M3W



Trim - Deep recessed directional
(White)
A80001-M5W



Trim - Curve recessed (White)
A80001-M8W



Trim - Key hole IP44 (White)
A80001-D5W



Trim - Pin hole IP44 (White)
A80001-D4W



Trim - Shallow directional
(White)
A80001-M7W



Trim - Shallow IP44 (White)
A80001-M1W



Trim - Surface cylinder (White)
A80001-C135W



DALI Control System
Control-DALI