

**MARVEL 4 (MAV-20011)**



**Product description**

Top Ø300 mm - Optic 90° - Supplied with a cylindrical, straight aluminium pole - Height option: 2.5 m



microPrim™

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass


- Driver is to be installed within the pole-head. Please contact the factory for pole compatibility.

**Optic**



G

**Product colour**



**Special finishes upon request**




**MARVEL 4 (MAV-20011)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	6 LED
<b>Power</b>	11 W
<b>Lumen</b>	1096 - 1153 lm
<b>Efficacy</b>	100 - 105 lm/W
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240V 50/60Hz
<b>Optic</b>	G

<b>Optic value</b>	120°X 92°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B1-U1-G0
<b>ULR</b>	1%
<b>ULOR</b>	1%
<b>CIE flux code n°3</b>	98
<b>Dimming type</b>	On/Off, DALI
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland

<b>Weight</b>	4.9 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>EPA (m2)</b>	0.030
<b>Cable</b>	One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable
<b>Through wiring</b>	Single cable entry
<b>Lens / Reflector / Optic</b>	High-efficiency PMMA lens, Clear toughened glass
<b>Variants (On/Off, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



**MARVEL 4 (MAV-20011)****Accessory**

---



---

2.5 m - Cylindrical, straight  
aluminium pole for MARVEL  
**APD125070-MARVEL**

---



---

DALI Control System  
**Control-DALI**

---