

LEGEND 2 (LE-40742-A)



Product description


With recessing box - Aluminium frame - IK08



Luminaire Structure


- Available with interchangeable aluminium or stainless steel grade 316 frames
- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal high-efficiency PMMA diffuser
- Integral control gear

Optic




G

Product colour



Special finishes upon request



LEGEND 2 (LE-40742-A)


Technical information

Material	Aluminium
Light source	60 LED
Power	14 W
Lumen	264 - 278 lm
Efficacy	19 - 20 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240V 50/60Hz

Optic	G
Optic value	65°x113°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U2-G1
ULR	16%
ULOR	16%
CIE flux code n°3	80
Dimming type	On/Off, 1-10V, DALI

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	2.3 kg
Operating temperature	-20 °C to 50 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal high-efficiency PMMA diffuser
Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

LE-40742-A



LEGEND 2 (LE-40742-A)

Accessory



DALI Control System
Control-DALI
