

URSA AIR

Manta aluminio reforzada M5102L



Reaction to fire
A2

Mineral wool blanket for thermal insulation of metal air conditioning ducts on the outside, in accordance with the standard UNE EN 14303.

DoP 34AIR34AK16091

Finish

- **Exterior:** reinforced kraft-aluminium complex and provided with tab.



0099/CPR/A43/0340 020/003544



Thermal Conductivity (λ90/90)	EN 12667 EN 12939	10°C	0,034 W/m·K
		24°C	0,036 W/m·K
		40°C	0,040 W/m·K
		60°C	0,045 W/m·K

Designation code: MW-EN 14303-T3-MV1

Reaction to fire (Euroclases)	EN 1350-1	A2-s1,d0
Steam Resistance	EN 12086	MV1 - 148,15 m²h Pa/mg
Nominal density approx.		22 Kg/m³
Specific heat approx. (CP)		800 J/Kg·K



Rolled

Code	Ud./Box	Length (m)	Width (m)	Thickness (mm)	m²/Box	Box/Pallet	m²/Pallet	Rt (m²·K/W)	Dis
2133462	1	18,00	1,15	30	20,70	18	372,60	0,88	S
2142679	1	11,50	1,15	45	13,23	18	238,05	1,32	S
2142812	1	11,50	1,15	50	13,23	18	238,05	1,32	S

Dis: availability S: stock C: consult Rt: thermal resistance (indicated at 10 °C)

