

## **DECLARATION OF PERFORMANCE (DoP)**

Nº DoP: LBM-FV-006C

22/04/2021

VERSIÓN 01

**1. Unique identification code of the product-type:**

Elastomer modified bitumen sheet with fibreglass reinforcement.

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

GLASDAN PRO 30 P TYPE (SBS/FG)

GLASDAN PRO 30 P

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer**

Bitumen reinforced sheet for roof waterproofing.

Bitumen reinforced sheet used as venting layer.

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA

Tel.: +34 949 88 82 10 - info@danosa.com

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

Not apply

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

2+

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: name and identification number of the notified body/ Performance/ under system (1+,1, 2+,3)/nº certificate and date of concession:**

AENOR: 0099

Evaluation of the factory production control

System 2+

Certificate of conformity of the factory production control, number and date: 0099/CPR/A85/0124 -

30/06/2022

UK Certificate of Conformity of the Factory Production Control, nº and date: UK 0836-CPR-23/F6682 –  
02/03/2023

External fire performance

System 3

AFITI LICOF

Reaction to fire

System 3

AFITI LICOF

8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
<b>External fire performance</b>	Broof(t1)	
<b>Reaction to fire</b>	E	
<b>Watertightness 2 kPa (Type A)</b>	Pass	
<b>Watertightness 60 kPa (Type B)</b>	Pass	
<b>Tensile strength:</b>		
<b>Maximum tensile force L*, (N/50 mm)</b>	550 ± 100	
<b>Maximum tensile force T*, (N/50 mm)</b>	300 ± 200	
<b>Elongation at maximum force L*, (%)</b>	NPD	
<b>Elongation at maximum force T*, (%)</b>	NPD	
<b>Resistance to root penetration</b>	Fails	
<b>Resistance to static loading, method A, (kg)</b>	NPD	
<b>Resistance to impact, method A or B, (mm)</b>	NPD	
<b>Tear resistance, (N)</b>	NPD	
<b>Resistance of joints</b>		EN 13707:2004+A2:2009; EN 13970:2004 + EN 13970:2004/A1:2006
<b>Peel strength (N/50mm)</b>	NPD	
<b>Shear resistance (N/50mm)</b>	NPD	
<b>Thermal durability</b>		
<b>Flow resistance at elevated temperature, (°C)</b>	100 ± 10	
<b>Flexibility at low temperature, (°C)</b>	-5 ± 5	
<b>UV, heat and water durability</b>		
<b>Flow resistance at elevated temperature, (°C)</b>	NPD	
<b>Flexibility at low temperature, (°C)</b>	NPD	
<b>Flexibility at low temperature, (°C)</b>	≤ -25	
<b>Thermal durability</b>		
<b>Factor de resistencia a la humedad, (μ)</b>	NPD	
<b>Chemical agents durability</b>		
<b>Factor de resistencia a la humedad, (μ)</b>	NPD	
<b>Factor de resistencia a la humedad, (μ)</b>	100000	
<b>Dangerous substances</b>	NPD	

L\* means longitudinal direction, T\* means transversal direction

NOTE 1: this product do not contains asbestos or tar.

NOTE 2: external fire performance is a system test, not a product test.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

10.

Name and function	Place and date of issue	Signature
Mónica de Velasco Bituminous Waterproofing Product Manager	Fontanar 04/12/2025	