

DECLARATION OF PERFORMANCE (DoP)

Nº DoP: PVC-HSF-002

18/12/2025

VERSION 03

1. Unique identification code of the product-type:

Synthetic PVC plasticized membrane reinforced with polyester net carrier and a 300gr geotextile a fleece backing.

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the PRC:

DANOPOL HSF 1.5

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Synthetic PVC plasticized membrane reinforced with polyester net carrier for roof waterproofing

Polymeric geosynthetic barrier

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5) of the PRC:

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA

Tel.: +34 949 88 82 10 - info@danosa.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the PRC:

Not apply

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

2+

7. Products covered by a harmonised standard: Name and number of the notified body / performed / Under system (1 +, 1, 2 +, 3) / certificate number and date of grant:

AENOR: 0099

Evaluation of the factory production control

System 2+

Certificate of conformity of the factory production control, nº & date: 0099/CPR/A85/0043 - 10/07/2008

Certificate of conformity of the factory production control, nº & date: 0099/CPR/A86/0025 - 02/10/2015

8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
External fire performance	Froof	
Reaction to fire	E	
Leaktightness	OK	
Tensile strength:		
Maximum tensile force L*, (N/50 mm)	≥ 1500	
Maximum tensile force T*, (N/50 mm)	≥ 1400	
Elongation at maximum force L*, (%)	≥ 25	
Elongation at maximum force T*, (%)	≥ 25	
Root resistance	OK	
Static load resistance, method A or B, (kg)	≥ 60	EN-13956:2012
Impact resistance method A or B, (mm)	≥ 800	
Tear resistance, (N)	≥ 400	
Seal Resistance		
Peel Strength (N/50mm)	≥ 300	
Shear resistance (N/50mm)	≥ 1500	
UV, heat and water durability ; Visual inspection, (Grade 0-3)	Pasa	
Heat and water durability 60 Kpa	Pasa	
Chemical products and water durability, 60 Kpa	Pasa	
Low temperature flexibility (° C)	≤ -30	
Tensile strength (L/T), N/mm²	20(-1)/19(-1)	
Static load resistance, kN	3,0 (-0,2)	
Permeability to liquids (m³/m²)/d	2.10-6 (-1.10-7)	
Durability, Resistance to weathering, %	Resist.Tracción L=≤1	EN 13361:2004;EN
	Resist.Tracción T=≤1	13361:2004/ A1:2006;
Durability, Resistance to oxidation, %	Alarg. L= ≤1	EN 13362; EN
	Alarg. T= ≤1	13491:2004; EN
Hazardous substances	Resist.Tracción L=≤1	13491:2004/ A1:2006
	Resist.Tracción T=≤1	
	Alarg. L= ≤1	
	Alarg. T= ≤1	
	NPD	

L* means longitudinal direction , T* means transverse direction

9.

The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

10.

Name and function	Place and Date of issue	Signature
Ignacio Mora - Single Ply Waterproofing Product Manager	FONTANAR 18/12/2025	