



Revision: 15/04/2020 Page 1 / 13

[X] Industrial [X] Professional

Date of printing: 15/04/2020 Version: 2 Revision: 15/04/2020 Previous revision: 26/04/2017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

DANOPRIMER EP COMP.B 1.1 **PRODUCT IDENTIFIER:**

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended uses (main technical functions):

Component of epoxy primer.

ses advised against:

This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'Intended or identified uses'.

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006

Contains CMR substances, categories 1A or 1B: Restricted to professional users. Forbidden to the general public. The restrictions do not apply to storage, keeping, treatment, filling into containers, or transfer from one container to another of the substances for export. See entry 28 and/or 29 and/or 30 in the Annex of the Regulation (EC) No. 552/2009~276/2010.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

DANOSA - DERIVADOS ASFÁLTICOS NORMALIZADOS, S.A

Polígono Industrial, Sector 9 - 19290 Fontanar (Guadalajara) ESPAÑA Phone: +34 949 888 210 - Fax: +34 949 888 223

E-mail address of the person responsible for the Safety Data Sheet:

e-mail: info@danosa.com

DANOSA ESPAÑA - Polígono Industrial, Sector 9 - 19290 Fontanar (Guadalajara) España - Tel. (+34) 949 888 210 DANOSA ESPAÑA - A-44. Salida 144. - 18640 Padul (Granada) España - Tel. (+34) 958 790 727

DANOSA PORTUGAL - Zona Industrial da Zicofa, Rua da Sismária, Lote 12. 2415-809 Leiria - Tel. (+351) 244 843 110

1.4 EMERGENCY TELEPHONE NUMBER: +34 902 422 452 (8:30-17:30 h.) (working hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1 **CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:**

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

ssification in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP):

DANGER: Skin Corr. 1B:H314 | Eye Dam. 1:H318 | Skin Sens. 1:H317 | Repr. 1B:H360Fd | Aquatic Acute 1:H400 | Aquatic Chronic 1:H410 | EUH071

Danger class	Classification of the mixture		Cat.	Routes of exposure	Target organs	Effects
Physicochemical: Not classified Human health: Environment:	Skin Corr. 1B:H314 Eye Dam. 1:H318 Skin Sens. 1:H317 Repr. 1B:H360Fd Aquatic Acute 1:H400 Aquatic Chronic 1:H410 EUH071	c) c) c) c) c)	Cat.1B Cat.1 Cat.1 Cat.1B Cat.1 Cat.1	Skin Eyes Skin - - Inhalation	Skin Eyes Skin Reproductive system - - Respiratory tract	Burns Serious lesions Allergy Fertility, Foetus - - Corrosion

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2 LABEL ELEMENTS:



This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP)

Hazard statements:

May damage fertility. Suspected of damage the unborn child. H360Fd

Causes severe skin burns and eye damage. H314

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract. recautionary statements:

P102-P405 Keep out of reach of children. Store locked up.

P201-P202 Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood.

P280F Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory

protection.

Wash contaminated clothing before reuse.

P301+P330+P331-P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. P303+P361+P353-P352-P312 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Wash with plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell.

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830



DANOPRIMER EP COMP.B



Index No. 603-069-00-0

< Autoclassified

Autoclassified

< REACH

Revision: 15/04/2020 Page 2 / 13

P305+P351+P338-P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a POISON CENTER or doctor. P273-P391-P501a

Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local

regulations.

Supplementary statements:

EUC028 Restricted to professional users.

Substances that contribute to classification: Tall-oil fatty acids/TETA-epoxy aduct

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine) 4,4 '-isopropylidenediphenol

OTHER HAZARDS: 2.3

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

Other physicochemical hazards: Vapours may form with air a mixture potentially flammable or explosive.

Other adverse human health effects: Prolonged exposure to vapours may produce transient drowsiness. Prolonged contact may cause skin dryness.

Other negative environmental effects: # Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCES: 3.1

Not applicable (mixture).

3.2 MIXTURES:

This product is a mixture.

Chemical description:

Modified Polyamine.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

40 < 50 %	Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether CAS: 186321-96-0, List No. 606-078-8 CLP: Danger: Skin Irrit. 2:H315 Eye Dam. 1:H318 Skin Sens. 1:H317 Aquatic Acute 1:H400 (M=1) Aquatic Chronic 1:H410 (M=1)	and triethylenetetramine Autoclassified < REACH
30 < 40 %	Benzyl alcohol CAS: 100-51-6, EC: 202-859-9 CLP: Warning: Acute Tox. (inh.) 4:H332 Acute Tox. (oral) 4:H302 Eye Irrit. 2:H319	Index No. 603-057-00-5 < Autoclassified
5 < 10 %	3-aminomethyl-3,5,5-trimethylcycb hexylamine CAS: 2855-13-2, EC: 220-666-8 CLP: Danger: Acute Tox. (skin) 4:H312 Acute Tox. (oral) 4:H302 Skin Corr. 1B:H314 Eye Dam. 1:H318 Skin Sens. 1A:H317 Aquatic Chronic 3:H412	Index No. 612-067-00-9 < Autoclassified
5 < 10 %	m-phenylenebis(methylamine) CAS: 1477-55-0 , EC: 216-032-5 CLP: Danger: Acute Tox. (inh.) 4:H332 Acute Tox. (oral) 4:H302 Skin Corr. 1B:H314 Skin Sens. 1B:H317 Aquatic Chronic 3:H412 EUH071	Autoclassified < REACH
5 < 10 %	4,4'-isopropylidenediphenol CAS: 80-05-7, EC: 201-245-8 CLP: Danger: Eye Dam. 1:H318 Skin Sens. 1:H317 Repr. 1B:H360F STOT SE (irrit.) 3:H335 Aquatic Chronic 2:H411	Index No. 604-030-00-0 < Autoclassified
2,5 < 5 %	Salicylic acid CAS: 69-72-7 , EC: 200-712-3 CLP: Danger: Acute Tox. (oral) 4:H302 Eye Dam. 1:H318 Repr. 2:H361d	Index No. 607-732-00-5 < ATP13
1 < 2 %	3,3-dimethylaminopropylamine CAS: 109-55-7, EC: 203-680-9 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (skin) 4:H312 Acute Tox. (oral) 4:H302 Skin Corr. 1B:H314 Eye Dam. 1:H318 Skin Sens. 1B:H317 STOT SE	Index No. 612-061-00-6 < Autoclassified

1 < 2 %

< 0,15 %

(irrit.) 3:H335

CLP: Danger: Skin Corr. 1C:H314 | Eye Dam. 1:H318

2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2, EC: 202-013-9

3-aminopropyltriethoxysilane CAS: 919-30-2, EC: 213-048-4

CLP: Danger: Acute Tox. (oral) 4:H302 | Skin Corr. 1B:H314 | Skin Sens. 1:H317

(!)

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.





Revision: 15/04/2020 Page 3 / 13

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 16/01/2020.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:
4,4'-isopropylidenediphenol, Repr.Cat.1B (Artide 57c), Decision: ED/01/2017, Endocrine disrupting properties having probable serious effects to human health (Article 57f), Decision: ED/30/2017 and Endocrine disrupting properties having probable serious effects to environment (Article 57f), Decision: ED/01/2018.

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 4: FIRST AID MEASURES

DESCRIPTION OF FIRST-AID MEASURES:



In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Lifequards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures		
Inhalation:	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces burning sensation, coughing, breathlessness and sore throat. Skin contact causes redness, burns and pain. Prolonged contact may cause skin dryness. # Contact with the eyes produces redness, pain, serious burns and loss of vision. If swallowed, causes severe burns on the lips, mouth, throat and oesophagus, with gastric	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.		
Skin:		Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners. In the case of skin reddening or rashes, contact a doctor immediately.		
Eyes:		Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.		
Ingestion:		If swallowed, seek immediate medical attention. Drink large quantities of water. Do not induce vomiting, due to the risk of perforation. Keep the patient at rest.		

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH A CUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: 4.3

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient. Antidotes and contraindications: Specific antidote not known.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, nitrogen oxides. Exposure to combustion or decomposition products may be a hazard to health.

5.3

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing va pours. Keep people without protection in opposition to the wind direction.

6.2 **ENVIRONMENTAL PRECAUTIONS:**

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

\danosa >
Building together



Revision: 15/04/2020 Page 4 / 13

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.

REFERENCE TO OTHER SECTIONS: 6.4

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Comply with the existing legislation on health and safety at work.

Handle with care, avoiding any discharge. Avoid any type of leakage or escape. Keep the container tightly closed.

Recommendations for the prevention of fire and explosion risks:

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.

- Flash point

- Upper/lower flammability or explosive limits

87* °C 1.3* - 13.0 % Volume 25°C

Recommendations for the prevention of toxicological risks:

#Pregnant women should not be employed in any process in which this product is used. Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8. Recommendations for the prevention of environmental contamination:

Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. Due to its corrosive properties, extreme precaution in the selection of materials for pumps, packages and lines should be taken. The floor must be waterproof and corrosion resistant, with a canal system allowing the liquid to be channelled towards a neutralising pit. The electrical equipment must be made of non-corrodible materials. For more information, see section 10.

Class of storage

According to current legislation.

Maximum storage period

24. months

Temperature interval Incompatible materials

5. °C, max: 40. °C (recommended). # min:

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials. Type of packaging:

According to current legislation.

Limit quantity (Seveso III): Directive 2012/18/EU:

- Named dangerous substances/mixtures: None
- Hazard categories and lower-/upperthreshold quantities in tonnes (t):
- · Physical hazards: Not applicable.
- · Health hazards: Not applicable
- · Environmental hazards: Very toxic to aquatic life with long lasting effects (E1) (100t/200t).
- Other hazards: Corrosive to the respiratory tract (O5) (50t/200t).
- Threshold quantity for the application of lower-tier requirements: 50 tons
- Threshold quantity for the application of upper-tier requirements: 200 tons

The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830



DANOPRIMER EP COMP.B



Revision: 15/04/2020 Page 5 / 13

7.3 SPECIFIC END USES:

#For the use of this product particular recommendations apart from that already indicated are not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assesing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2018	<u>Year</u>	TLV-TWA		TLV-STEL		<u>Remarks</u>
m-phenylenebis(methylamine)	1977	ppm -	mg/m3 -	ppm -	mg/m3 0.10C	Internal value A3 , Skin , BEI

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

C - Ceiling value: The concentration that should not be exceded during any part of the working exposure.

Skin - Danger of cutaneous absorption.

A3 - Carcinogenic in animals.

BEI - Biological exposure index (biological monitoring).

<u>Dermal (Vd):</u> Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be or equal or greater importance even that inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

BIOLOGICAL LIMIT VALUES:

Not available

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

	 	DNEL Oral mg/kg bw/d	
	 	DNEL Eyes mg/cm2	

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

SAFETY DATA SHEET (REACH)In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830



DANOPRIMER EP COMP.B

Predicted no-effect concentration, terrestrial organisms:
- Air, soil and effects for predators and humans:
Not available (without data of registration REACH).



Revision: 15/04/2020 Page 6 / 13

PNEC Oral

mg/kg dw/d

PREDICTED NO-EFFECT CONCENTRATION (PNEC):			
	PNEC Fresh water mg/l		PNEC Intermittent mg/l
	PNEC STP mg/l	PNEC Sediments mg/kg dw/d	PNEC Sediments mg/kg dw/d

PNEC Air

mg/m3

PNEC Soil

mg/kg dw/d





Revision: 15/04/2020 Page 7 / 13

8.2 EXPOSURE CONTROLS:

ENGINEERING MEASURES:











Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: Install water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: Install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, deaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

provided by the manu	facturers of PPE.
Mask:	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety goggles:	Safety goggles for chemicals, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	Face shield against liquid splashes (EN166), advisable when there is a risk of spillage, diffusion or atomization of the liquid.
Gloves:	Neoprene rubber gloves (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	Neoprene rubber boots (EN347).
Apron:	No.
Clothing:	Clothing resistant to corrosive products will have to be worn.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

- Water Management Act: This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

<u>Emissions to the atmosphere:</u> Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

- VOC (product ready for use*): # It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory j)
Two-pack performance coating, solvent-borne. VOC (product ready for use*) (producto auxiliar (endurecedor).): 82.4* g/l* (VOC

max. 500. g//* starting from 01.01.2010).

- VOC (industrial installations): # If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 30.0% Weight, VOC (supply): 8.0% Weight, VOC: 5.5% C (expressed as carbon), Molecular weight (average): 132.0, Number C atoms (average): 7.6.





Revision: 15/04/2020 Page 8 / 13

```
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
        INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:
        Appearance
         Physical state
                                                                            Clear liquid.
        - Colour
                                                                            Brown.
        - Odour
                                                                            Characteristic
        - Odour threshold
                                                                            Not available (mixture).
        pH-value
        - pH
                                                                            Alkaline
        Change of state
        - Melting point
                                                                            Not applicable (mixture).
                                                                                               °C at 760 mmHg
        - Boiling interval
                                                                                 123* - 312*
        Density
          Vapour density
                                                                                       3.61* at 20°C 1 atm.
                                                                                                                           Relative air
                                                                                 1.03 \pm 0.02 at 20/4°C

    Relative density

                                                                                                                           Relative water
        Stability
                                                                            Not available (technical impossibility to obtain the data).

    Decomposition temperature

        Viscosity:
                                                                              1000. ± 400. cps 23°C
390. mm2/s at 40°C
        - Dynamic viscosity
         Kinematic viscosity
        Volatility:
         Evaporation rate
                                                                            # Not available (lack of data).
                                                                                       0.25* mmHg at 3
0.26* kPa at 50°C
          Vapour pressure
                                                                                                        at 20°C
         Vapour pressure
        Solubility(ies)
          Solubility in water:
                                                                            # Not miscible
        - Liposolubility
                                                                            Not available (mixture untested).
         Partition coefficient: n-octanol/water
                                                                            Not applicable (mixture).
        Flammability:
        - Flash point
                                                                                                                           # CLP 2.6.4.3.
                                                                                 1.3* - 13.0 % Volume 25°C
        - Upper/lower flammability or explosive limits
         Autoignition temperature
                                                                            # Not available
        Explosive properties
        Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.
        Oxidizing properties
        Not classified as oxidizing product.
        *Estimated values based on the substances composing the mixture.
9.2
        OTHER INFORMATION:
                                                                                         68.9
         Solids
                                                                                               % Weight
        VOC (supply)VOC (supply)
                                                                                          8.0 % Weight
                                                                                               g/I
        The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the
        corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and
        environment, see sections 7 and 12.
SECTION 10: STABILITY AND REACTIVITY
10.1
        REACTIVITY:
        Corrosivity to metals: Not available.
        Pyrophorical properties: It is not pyrophoric.
10.2
        CHEMICAL STABILITY:
        Stable under recommended storage and handling conditions.
10.3
        POSSIBILITY OF HAZARDOUS REACTIONS:
        Possible dangerous reaction with reducing agents, oxidizing agents, acids, alkalis, metals.
10.4
        CONDITIONS TO AVOID:
        Heat: Keep away from sources of heat.
Light: If possible, avoid direct contact with sunlight.
             The product is not affected by exposure to air, but should not be left the containers open.
        Humidity: Avoid extreme humidity conditions.

Pressure: Not relevant.
        Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough
        handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and
        download operations.
10.5
        INCOMPATIBLE MATERIALS:
        Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.
        HAZARDOUS DECOMPOSITION PRODUCTS:
10.6
        As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides.
```





Revision: 15/04/2020 Page 9 / 13

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients: Tall-oil fatty acids/TETA-epoxy aduct Benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclo hexylamine m-phenylenebis(methylamine) 4,4'-isopropylidenediphenol Salicylic acid 3,3-dimethylaminopropylamine 2,4,6-tris(dimethylaminomethyl)phenol 3-aminopropyltriethoxysilane	LD50 (OECD 401) mg/kg bw oral > 2000. Rat 1620. Rat 1030. Rat 930. Rat 3250. Rat 891. Rat 410. Rat 2169. Rat 1780. Rat	LD50 (OECD 402) mg/kg bw cutaneous > 2000. Rat > 2000. Rabbit > 2000. Rabbit 3100. Rabbit 3000. Rabbit > 2000. Rabbit 1002. Rabbit 1002. Rabbit > 2000. Rat 4000. Rabbit	LC50 (OECD 403) mg/m3·4h inhalation > 8800. Rat > 5010. Rat > 1340. Rat > 4310. Rat > 7350. Rat
Estimates of acute toxicity (ATE) for individual ingredients: Benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) Salicylic acid 3,3-dimethylaminopropylamine 3-aminopropyltriethoxysilane	ATE mg/kg bw oral 1620. 1030. 930. 891. 410. 1780.	ATE mg/kg bw cutaneous > 2000	ATE mg/m3·4h inhalation 11000.* 11000.* Vapours

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results. (-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available

Lowest observed adverse effect level

INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 2000 mg/kg bw	-	#Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).





Revision: 15/04/2020 Page 10 / 13

CORROSION	/ IRRITATION .	/ SENSITISATION :

SOUNDSTONY INITIATION / SENSITION I								
Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria				
Respiratory corrosion/irritation:	Respiratory tract	-	CORROSIVE: Corrosive to the respiratory tract.	GHS/CLP 1.2.6.				
Skin corrosion/irritation:	Skin	Cat.1B	CORROSIVE: Causes severe skin burns.	GHS/CLP 3.2.3.3.				
Serious eye damage/irritation:	Eyes	Cat.1	DAMAGE: Causes serious eye damage.	GHS/CLP 3.3.3.3.				
Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.				
Skin sensitisation:	Skin	Cat.1	SENSITISING: May cause an allergic skin reaction.	GHS/CLP 3.4.3.3.				

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria	
Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.	

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET OR GANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Not classified as a dangerous product for target organs (based on available data, the classification criteria are not met).

Carcinogenic effects: It is not considered as a carcinogenic product.

Genotoxicity: It is not considered as a mutagenic product.

Toxicity for reproduction

This preparation contains the following ingredients which can be toxic for human reproduction: 4,4'-isopropylidenediphenol (Cat.1B)

Salicylic acid (Cat.2)

Effects via lactation: Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: # Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine particles are skin and respiratory tract irritants. Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat and other effects may be the same as described in the exposure to vapours. Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: m-phenylenebis(methylamine). Basic toxicokinetics: Not available.

ADDITIONAL INFORMATION:

Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine partides are skin and respiratory tract irritants.





Revision: 15/04/2020 Page 11 / 13

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).

171	TOXICITY:
12.1	I IUNICIII.

<u> </u>			
Acute toxicity in aquatic environment for individual ingredients: Tall-oil fatty acids/TETA-epoxy aduct Benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclo hexylamine m-phenylenebis (methylamine)	LC50 (OECD 203) mg/l·96hours > 1.8 Fishes 460. Fishes 110. Fishes > 88. Fishes	EC50 (OECD 202) mg/l·48hours 230. Daphnia > 23. Daphnia > 15. Daphnia	EC50 (OECD 201) mg/l·72hours 0.77 Algae 770. Algae > 37. Algae > 20. Algae
4,4'-isopropylidenediphenol Salicylic acid	> 11. Fishes 1370. Fishes	> 10. Daphnia 870. Daphnia	> 1.4 Algae > 100. Algae
3,3-dimethylaminopropylamine	122. Fishes	> 59. Daphnia	> 53. Algae
2,4,6-tris(dimethylaminomethyl)phenol	180. Fishes	250. Daphnia	> 84. Algae
3-aminopropyltriethoxysilane	934. Fishes	331. Daphnia	603. Algae
No observed effect concentration	NOEC (OECD 210)	NOEC (OECD 211)	NOEC (OECD 201)
m-phenylenebis(methylamine) Salicylic acid	mg/r zoddys	4.7 Daphnia > 10. Daphnia	11. Algae

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
Acute aquatic toxicity:	Cat.1	VERY TOXIC: Very toxic to aquatic life.	GHS/CLP 4.1.3.5.5.3.
Chronic aquatic toxicity:	Cat.1	VERY TOXIC: Very toxic to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components. CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

Aerobic biodegradation	DQO	%DBO/DQO	Biodegradability
for individual ingredients :	mgO2/g	5 days 14 days 28 days	
Tall-oil fatty acids/TETA-epoxy aduct		9.	Not easy
Benzyl alcohol	2515.	~ 62. ~ 86. ~ 95.	Easy
3-aminomethyl-3,5,5-trimethylcyclohexylamine		8.	Not easy
m-phenylenebis(methylamine)		8. 29. 49.	Not easy
4,4'-isopropylidenediphenol		63. 89.	Easy
Salicylic acid	811.		Easy
3,3-dimethylaminopropylamine			Easy
2,4,6-tris(dimethylaminomethyl)phenol	1260.	~ 4.	Not easy
3-aminopropyltriethoxysilane		67.	Not easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

12.3 **BIOACCUMULATIVE POTENTIAL:**

Not available.

Bioaccumulation for individual ingredients :	log Pow	BCF L/kg	<u>Potential</u>
Tall-oil fatty acids/TETA-epoxy aduct	3,38	L/Kg	Not available
Benzyl alcohol	1.10	1.4 (calculated)	Not available
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.990	8.4 (calculated)	Not available
	0.180	3.2 (calculated)	Not available
m-phenylenebis(methylamine)		()	
4,4´-isopropylidenediphenol	3.32	70. (calculated)	Not available
Salicylic acid	2.25	3.2 (calculated)	Not available
3,3-dimethylaminopropylamine	-0.350	3.2 (calculated)	Not available
2,4,6-tris(dimethylaminomethyl)phenol	0.770	3.2 (calculated)	Not available
3-aminopropyltriethoxysilane	1.70	3.2 (calculated)	Not available

12.4 MOBILITY IN SOIL:

Not available.

Mobility for individual ingredients:	log Koc	Constant of Henry Pa·m3/mol 20°C	Potential
Tall-oil fatty acids/TETA-epoxy aduct Benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) 4,4 '-isopropylidenediphenol Salicylic acid 3,3-dimethylaminopropylamine 2,4,6-tris(dimethylaminomethyl)phenol 3-aminopropyltriethoxysilane	2.99 1.10 1.59 0.960 3.09 1.57 0.590 1.32 1.07	0.034 (calculated) 0.00045 (calculated) 0.00074 (calculated)	Not available Not available Not available Not available Not available Not available Not available Not available Not available

\danosa >	С
Building together	



Revision: 15/04/2020 Page 12 / 13

RESULTS OF PBT AND VPVB ASSESMENT: 12.5 Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfil the PBT/vPvB criteria.

OTHER ADVERSE EFFECTS 12.6

Ozone depletion potential: Not available.

Photochemical ozone creation potential: Not available.

Earth global warming potential: In case of fire or incineration liberates CO2.

Endocrine disrupting potential: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014: 13.1

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see

Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

UN NUMBER: 2735 14.1

14.2 UN PROPER SHIPPING NAME:

AMINES, LIQUID, CORROSIVE, N.O.S. | POLYAMINES, LIQUID, CORROSIVE, N.O.S. (contains 3-aminomethyl-3,5,5-trimethylcyclohexylamin

14.3 TRANSPORT HAZARD CLASS(ES):

> Transport by road (ADR 2019) and Transport by rail (RID 2019):

III - Packing group: - Classification code: C7 Tunnel restriction code: (E)

3, max. ADR 1.1.3.6. 1000 L - Transport category: 5 L (see total exemptions ADR 3.4) - Limited quantities: Consignment paper. - Transport document:

- Instructions in writing: ADR 5.4.3.4

Transport by sea (IMDG 39-18):

Class: - Packing group: III F-A,S-B - Emergency Sheet (EmS): - First Aid Guide (MFAG): 320 - Marine pollutant: Yes.

- Transport document: Shipping Bill of lading.

Transport by air (ICAO/IATA 2020):

Class: - Packing group: III

Air Bill of lading. - Transport document:

Transport by inland waterways (ADN):

Not available.

PACKING GROUP: 14.4 See section 14.3

14.5

ENVIRONMENTAL HAZARDS:

Classified as hazardous for the environment.

14.6 SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation. Keep separated from foodstuffs.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE: 14.7 # Not applicable.


SECTION 15: REGULATORY INFORMATION

EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC 15.1


The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use: See section 1.2















Revision: 15/04/2020 Page 13 / 13

Tactile warning of danger: Not applicable (product for professional or industrial use).

Child safety protection: Not applicable (product for professional or industrial use).

VOC information on the label

#Contains VOC max. 82. g/l - The limit value 2004/42/CE-IIA cat. j) for the product ready for use is VOC max. 500. g/l (2010).

OTHER REGULATIONS:

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations

#The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 **CHEMICAL SAFETY ASSESSMENT:**

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: OTHER INFORMATION

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2018/1480 (CLP), Annex III: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. H360F May damage fertility. H361d Suspected of damage the unborn child.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- · European Chemicals Agency: ECHA, http://echa.europa.eu/
- · Access to European Union Law, http://eur-lex.europa.eu/
- · Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- · Threshold Limit Values, (AGCIH, 2017).
- · European agreement on the international carriage of dangerous goods by road, (ADR 2019)
- · International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- · CLP: Europeán regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- · EINECS: European Inventory of Existing Commercial Chemical Substances.
- · ELINCS: European List of Notified Chemical Substances.
- · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials. · SVHC: Substances of Very High Concern.
- · PBT: Persistent, bioaccumulable and toxic substances.
- · vPvB: Very persistent and very bioaccumulable substances.
- · VOC: Volatile Organic Compounds
- DNEL: Derived No-Effect Level (REACH).
- · PNEC: Predicted No-Effect Concentration (REACH).
- · LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- · UN: United Nations Organisation.
- · ADR: European agreement concerning the international carriage of dangeous goods by road.
- · RID: Regulations concerning the international transport of dangeous goods by rail.
- · IMDG: International Maritime code for Dangerous Goods.
- · IATA: International Air Transport Association.
- · ICAO: International Civil Aviation Organization.

AFETY DATA SHEET REGULATIONS

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

Revision **HISTORIC** Version: 1 26/04/2017 Version: 2 15/04/2020

Changes since previous Safety Data Sheet:

#Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.