

DECLARATION OF PERFORMANCE (DoP)

Nº DoP: GEO-PY-0004

11/11/2020

VERSION 07

1. Unique identification code of the product-type:

POLYESTER GEOTEXTILE

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the PRC:

DANOFELT PY 300

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Polyester geotextile for application in: roads, traffic routes, railways, earthworks, foundations, retaining structures, drainage systems, erosion control, reservoirs, dams, canals, tunnels, underground structures, solid waste landfills, and projects for liquid waste containers.

Intended uses: "F", "F+S", "F+S+D" y "P"

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5) of the PRC:

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA

Tel.: +34 949 88 82 10 - info@danosa.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the PRC:

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

2+

7. Products covered by a harmonised standard: Name and number of the notified body / performed / Under system (1 +, 1, 2 +, 3) / certificate number and date of grant:

AENOR:0099

Evaluation of Factory Production Control

System 2 +

Certificate of Factory Production Control, number and date:: 0099/CPR/A42/0046/0047/0048/0049 - 05/03/2007


8. Declared performance:

| Essential Characteristics | Performance | Harmonized Technical Specification |
|--|--|------------------------------------|
| Tensile strength: | | |
| Maximum tensile force L*, (kN/m) | 4,4 (-0,4) | EN-13249:2016 |
| Maximum tensile force T*, (kN/m) | 4,4 (-0,4) | EN-13250:2016 |
| Elongation at maximum force L*, (%) | 120 ± 30 | EN-13251:2016 |
| Elongation at maximum force T*, (%) | 120 ± 30 | EN-13252:2016 |
| Static puncture resistance (CBR), (kN) | 1,1 (-0,3) | EN-13253:2016 |
| Dynamic puncture resistance (cone) (mm) | 8 (+3) | EN-13254:2016 |
| Aperture measurement, (µm) | 90 ± 20 | EN-13255:2016 |
| Water permeability, (m / s) | 0,03154 (-0,005) | EN-13256:2016 |
| Water flow capacity in the plane, (m²/s) | 20 kPa: 1,9*10 ⁻⁶ (-0,2*10 ⁻⁷) | EN-13257:2016 |
| Protection effectiveness, (kN/m²) | 15,5*10 ³ (-0,3*10 ³) | EN-13265:2016 |
| Durability, (years) | >25; natural soil; 4<pH<9;T<25°C | |

L* means longitudinal direction , T* means transverse direction

The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 8.

This DoP is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

| Name and function | Place and Date of issue | Signature |
|---|-------------------------|---|
| Carlos Castro Martín Technical responsible | Fontanar 11/11/2020 |  |