

## **DECLARATION OF PERFORMANCE (DoP)**

Nº DoP: TEC-003

23/07/2026

VERSION 02

1. **Unique identification code of the product-type:**

ARGOTEC REPARACIÓN R4

2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:**

Date and/or batch number: see bag

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Plaster mortar for current use (GP)

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR:**

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA

(SPAIN)

Tel.: +34 949 88 82 10 - info@danosa.com

5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the CPR:**

Not relevant

6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 4

7. **Products covered by a harmonised standard: Name and number of the notified body:**

8. **Declared performance:**

| Essential characteristics                     | Performances                                    | Harmonised technical specification |
|-----------------------------------------------|-------------------------------------------------|------------------------------------|
| Chloride ion content                          | $\leq 0,05\%$                                   | EN-1504-3                          |
| Resistance to compresion 28 days              | $\geq 45$ Mpa                                   |                                    |
| Water absorption                              | $\leq 0,5$ Kg/m <sup>2</sup> min <sup>0,5</sup> |                                    |
| Reaction to fire                              | A1                                              |                                    |
| Adherence                                     | PND                                             |                                    |
| Resistance to carbonation                     | PND                                             |                                    |
| Modulus of elasticity                         | PND                                             |                                    |
| Thermal compatibility - Part 1: Freeze - thaw | PND                                             |                                    |
| Hazardous substances                          | See MSDS                                        |                                    |

PND: Performance not determined

9. The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

- 10.
- | Name and function                              | Place and Date of issue      | Signature                                                                             |
|------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------|
| Helder Gonçalves, technical expert for mortars | Fontanar-Guadalajara (Spain) |  |
|                                                | 23/07/2026                   |                                                                                       |