

DECLARATION OF PERFORMANCE (DoP)

N° DoP: DP-003

20/03/2023

VERSION 01

1. Unique identification code of the product-type:

DANOCRET PROTECT 200

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Cimentitious PCC membrane impermeable by crystallization in capillaries

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

General waterproofing and surface protection of concrete and mortar

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR:

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA (SPAIN)

Tel.: +34 949 88 82 10 - info@danosa.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the CPR:

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

Sistema 4

7. Products covered by a harmonised standard: Name and number of the notified body:

0

0

0

0

8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	NPD	EN 1504-2:2005
CO2 permeability	Clase II	
Water vapor permeability	Clase I	
Capillary absorption and water permeability	$W \leq 0,1 \text{ Kg/m}_2 \cdot \text{h}^5$	
Direct tensile adhesion	$\geq 0,8 \text{ Mpa}$	
Adhesion after thermal compatibility	$\geq 0,8 \text{ Mpa}$	
Resistance to cracking static method 0°C	Clase A3	
Water impermeability	no penetration	
Initial adhesion	$\geq 0,5 \text{ Mpa}$	


Adhesión after immersion in water	≥ 0,5 Mpa	EN 14891:2012 + A1:2013
Adhesión after heat	≥ 0,5 Mpa	
Adhesión after freeze / thaw cycles	≥ 0,5 Mpa	
Adhesión after immersion in lime water	≥ 0,5 Mpa	
Crack elongation capacity	≥ 0,75 mm	
Additional Characteristics	MC 01P	
Dangerous substances	Ver FDS	

NPD: No Performance Determined

9. The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

10.

Name and function	Place and Date of issue	Signature
José Luis Zurita Urbano , technical expert for mortars	Fontanar-Guadalajara (Spain)	
	21/12/2022	