

DECLARATION OF PERFORMANCE (DoP)

Nº DoP: LIQ-005

25/10/2023

VERSIÓN 04

1. **Unique identification code of the product-type:**
DANOPRIMER EPS
2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**
Solvent-free bicomponent epoxy primer, suitable for porous substrates with residual moisture - See batch number on the package
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer**
Primer, bicomponent epoxy based leveling mortar. Conforms to EN 13813 SR-B2,0-AR0,5-IR14 as a resin for coatings. Conforming to EN13813 SR-B2.0 as primer.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**
DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA
Tel.: +34 949 88 82 10 - info@danosa.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
Not apply
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
System 3 for waterproofing
7. **In case of the declaration of performance concerning a construction product covered by a harmonised standard: name and identification number of the notified body/ Performance/ under system (1+,1, 2+,3)/nº certificate and date of concession:**

Test Report EN 13813:2014

Nº 16/11721-
334M1


APPLUS

8. Declared performance:

Essential characteristics	Performances	Harmonised technical specification
Emission of corrosive substances	SR	EN 13813:2014
Abrasion resistance	AR 0,5	
Adherence	> 2,9 Mpa (B 2,0)	
Impact resistance	≥ IR14	
Acoustic isolation	NPD*	
Acoustic absorption	NPD*	
Reaction to fire	Clase Bfl-s1	
Thermal resistance	NPD*	
Chemical resistance	NPD*	
Dangerous substances	See MSDS	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name and function	Place and date of	Signature
Daniel Andaluz García	Fontanar	
Product Manager Liquid Waterproofing	25/10/2023	