

DECLARATION OF PERFORMANCE (DoP)

Nº DoP: LIQ-019

12/01/2022

VERSIÓN 01

1. **Unique identification code of the product-type:**
DANOPUR LT TRANSPARENTE
2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**
Pure bicomponent polyurea membrane - See batch number on packaging
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer**
Waterproofing, solvent-free, elastic and quick curing product for waterproofing and surface protection for concrete in civil engineering and roofing.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**
DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA
Tel.: +34 949 88 82 10 - info@danosa.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
Not apply
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
System 4
7. **In case of the declaration of performance concerning a construction product covered by a harmonised standard: name and identification number of the notified body/ Performance/ under system (1+,1, 2+,3)/nº certificate and date of concession:**

Informe de ensayo UNE-EN 1504-2:2005


90-20-0277

TSUS

8. Declared performance:

Essential characteristics		Performance	Harmonised technical specification
Bond strength by pull-off		$\geq 1,5$ Mpa	EN 1504-2:2005
Water-vapour transmission		Clase I: SD < 5	
Liquid water permeability		$W < 0,1 \text{ kg/m}^2 \cdot \text{h} \cdot 0,5$	
Carbon dioxide permeability		SD > 50	
Resistance to impact		NPD	
Taber abrader		NPD	
Resistance to temperature shock		NPD	
Crack bridging properties	Static method (-10°C)	NPD	
	Dyanmic method (-10°C)	NPD	
Reaction to fire		Clase F	
Resistance to severe chemical attack (group 1, 3, 9, 10, 11, 12)		NPD	
Dangerous substances		See MSDS	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in
10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name and function	Place and date of	Signature
Jorge Colchero Vázquez	Fontanar	
Product manager Liquid waterproofing	12/01/2022	