

DECLARATION OF PERFORMANCE (DoP)

Nº DoP: DP-001
02/09/2025
VERSION 02

1. Unique identification code of the product-type:

DANOCRET PROTECT 500 FLEX

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Waterproof flexible cementitious membrane PCC

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

General waterproofing and surface protection of concrete and mortar

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR:

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA (SPAIN)

Tel.: +34 949 88 82 10 - info@danosa.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the CPR:

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

Sistema 3

7. Products covered by a harmonised standard: Name and number of the notified body:

AFITI (nº 1168)

APPLUS (nº 0370)


8. Declared performance:

Essential Characteristics	Performances	Harmonized Technical Specification
Reaction to fire	B s2 d0	EN 1504-2:2004
CO2 permeability	Clase III	
Water vapor permeability	Clase II	
Capillary absorption and water permeability	$W \leq 0,1 \text{ Kg/m}_2 \cdot \text{h}^{\frac{1}{2}}$	
Direct tensile adhesion	$\geq 0,8 \text{ Mpa}$	
Adhesion after thermal compatibility	$\geq 0,8 \text{ Mpa}$	
Resistance to cracking static method 0°C	Clase A5	
Water impermeability	pas de pénétration	EN 14891:2012 + AC:2012
Initial adhesion	$\geq 0,5 \text{ Mpa}$	
Adhesion after immersion in water	$\geq 0,5 \text{ Mpa}$	
Adhesion after heat	$\geq 0,5 \text{ Mpa}$	
Adhesion after freeze / thaw cycles	$\geq 0,5 \text{ Mpa}$	
Adhesion after immersion in lime water	$\geq 0,5 \text{ Mpa}$	
Crack elongation capacity	$\geq 0,75 \text{ mm}$	
Additional Characteristics	MC 02P	
Dangerous substances	Ver FDS	

NPD: No Performance Determined

9. The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

10.	Name and function	Place and Date of issue	Signature
	Helder Gonçalves Product Manager	Fontanar-Guadalajara (Spain)	
		02/09/2025	