## **DECLARATION OF PERFORMANCE (DoP)**

Nº DoP: LIQ-009 20/07/2021 VERSIÓN 03

1. Unique identification code of the product-type:

**DANOFLOOR PU 300** 

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Elastic bicomponent polyurethane resin for rolling, self-leveling and sealed layers. - See batch number on the package

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Conforms to EN 13813 SR-B2,0-AR0,5-IR14 as a polyurethane resin for coating

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

DANOSA- POL. IND. SECTOR 9-19290 FONTANAR-GUADALAJARA-ESPAÑA Tel.: +34 949 88 82 10 - info@danosa.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not apply

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 for waterproofing

In case of the declaration of performance concerning a construction product covered by a harmonised standard: name and identification number of the notified body/ Performance/ under system (1+,1, 2+,3)/nº certificate and date of concession:

Reaction to fire CEN TS 1187:2013 17/14269-1243 APPLUS
Test Report EN 13813:2014 17/14362-940 APPLUS

## 8. Declared performance:

Essential characteristics	Performances	Harmonised technical	
Emission of corrosive substances	SR		
Abrasion resistance	AR 0,5		
Adherence	2,4 Mpa (B 2,0)		
Impact resistence	≥ IR14		
Acoustic isolation	NPD*	EN 13813:2014	
Acoustic absorption	NPD*		
Reaction to fire	Clase Bfl-s1		
Thermal resistance	NPD*		
Chemical resistance	NPD*		
Dangerous substances	See	See MSDS	

- **9.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
- 10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name and function	Place and date of issue	Signature
Jorge Colchero Vázquez	Fontanar	***
Product manager Liquid waterproofing	20/07/2021	