



Building together

REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1

PRODUCT IDENTIFIER:

REVESTIDAN SATE ACRILICO

1.2

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended uses (main technical functions):

Industrial

X

Professional

X

Consumers

Liquid paint.

Sectors of use:

Industrial manufacturing (SU3), Industrial.

Consumer uses (SU21),

Professional uses (SU22),

Uses advised against:

This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses".

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

Not restricted.

1.3

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

DANOSA - DERIVADOS ASFÁLTICOS NORMALIZADOS, S.A.

Polígono Industrial, Sector 9 - 19290 Fontanar (Guadalajara) ESPAÑA

Phone number: 949888210 - Fax: 949 888 223 - www.danosa.com

- E-mail address of the person responsible for the Safety Data Sheet:

info@danosa.com

1.4

EMERGENCY TELEPHONE NUMBER:

902 422 452 8:30-17:30 h

SECTION 2 : HAZARDS IDENTIFICATION

2.1

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

Classification in accordance with Regulation (EU) No. 1272/2008~2022/692 (CLP):

Aquatic Chronic 3:H412

Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Physicochemical:					
Not classified					
Human health:					
Not classified					
Environment:	Aquatic Chronic 3:H412 c)	Cat.3	-	-	-

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2

LABEL ELEMENTS:

This product is labelled in accordance with Regulation (EU) No. 1272/2008~2022/692 (CLP).

- Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P273-P501 Avoid release to the environment. Dispose of contents/container as hazardous waste.

- Supplementary statements:

EUH208 Contains 2-octyl-2H-isothiazol-3-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1). May produce an allergic reaction.

- Contains Diuron (ISO), 2-octyl-2H-isothiazol-3-one to protect the film.

- Substances that contribute to classification:

None in a percentage equal to or higher than the limit for the name.

2.3

OTHER HAZARDS:

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

- Other physicochemical hazards:

No other relevant adverse effects are known.

- Other adverse human health effects:



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

SECTION 4: FIRST AID MEASURES

4.1	DESCRIPTION OF FIRST AID MEASURES:
-----	------------------------------------



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation:	It is not expected that symptoms will occur under normal conditions of use.	Should there be any symptoms, transfer the person affected to the open air.
Skin:	It is not expected that symptoms will occur under normal conditions of use.	Remove contaminated clothing.Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Eyes:	It is not expected that symptoms will occur under normal conditions of use.	Remove contact lenses.Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart.If irritation persists, consult a physician.
Ingestion:	If swallowed in high doses, may cause gastrointestinal disturbances.	Do not induce vomiting, due to the risk of aspiration.Keep the patient at rest.

4.2	MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:
-----	--

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3	INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
-----	---

Notes to physician:

Treatment should be directed at the control of symptoms and the clinical condition of the patient...

Antidotes and contraindications:

Specific antidote not known.

SECTION 5: FIREFIGHTING MEASURES

5.1	EXTINGUISHING MEDIA:
-----	----------------------

Extinguishing powder or CO2.

5.2	SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:
-----	--

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, nitrogen oxides, isocyanate vapors, traces of hydrocyanic acid, halogenated compounds, sulfur oxides. Exposure to combustion or decomposition products may be a hazard to health.

5.3	ADVICE FOR FIREFIGHTERS:
-----	--------------------------

Special protective equipment:

Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations:

Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
- 6.2 ENVIRONMENTAL PRECAUTIONS:
Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
- 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:
Contain and mop up spills with absorbent materials (sawdust, earth, sand, vermiculite, diatomaceous earth, etc.). Keep the remains in a closed container.
- 6.4 REFERENCE TO OTHER SECTIONS:
For contact information in case of emergency, see section 1.
For information on safe handling, see section 7.
For exposure controls and personal protection measures, see section 8.
For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

- 7.1 PRECAUTIONS FOR SAFE HANDLING:
Comply with the existing legislation on health and safety at work.
- General recommendations:
Avoid any type of leakage or escape. Keep the container tightly closed.
- Recommendations for the prevention of fire and explosion risks:
Not applicable.
- Recommendations for the prevention of toxicological risks:
Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.
- Recommendations for the prevention of environmental contamination:
Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
Forbid the entry to unauthorized persons. Keep out of reach of children. Keep away from sources of heat. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
- Class of store:
According to current legislation.
- Maximum storage period:
24 Months.
- Temperature interval:
min: 5 °C, max: 40 °C (recommended).
- Incompatible materials:
Keep away from oxidizing agents, acids, alkalis, reducing agents.
- Type of packaging:
According to current legislation.
- Limit quantity (Seveso III): Directive 2012/18/EU:
Not applicable (product for non industrial use).
- 7.3 SPECIFIC END USE(S):
For the use of this product particular recommendations apart from that already indicated are not available.



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA	mg/m ³	WEL-STEL	mg/m ³	Remarks
Diuron (ISO)	1996	1	10	-	-	A4
2-octyl-2H-isothiazol-3-one	-	-	0,05	-	-	Recommended

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

A4 - Non classified as carcinogenic in humans.

- BIOLOGICAL LIMIT VALUES:

Not established

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS: - Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/kg bw/d	DNEL Oral mg/kg bw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
2-octyl-2H-isothiazol-3-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
Diuron (ISO)	- (a) 0,17 (c)	- (a) 5,79 (c)	- (a) - (c)
- DERIVED NO-EFFECT LEVEL, WORKERS: - Local effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/cm ²	DNEL Eyes mg/cm ²
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
2-octyl-2H-isothiazol-3-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
Diuron (ISO)	- (a) - (c)	- (a) - (c)	- (a) - (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/kg bw/d	DNEL Eyes mg/kg bw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
2-octyl-2H-isothiazol-3-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
Diuron (ISO)	- (a) - (c)	- (a) - (c)	- (a) - (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC: - Local effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/cm ²	DNEL Eyes mg/cm ²
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
2-octyl-2H-isothiazol-3-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
Diuron (ISO)	- (a) - (c)	- (a) - (c)	- (a) - (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

- PREDICTED NO-EFFECT CONCENTRATION, AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:	PNEC Fresh water mg/l	PNEC Marine mg/l	PNEC Intermittent mg/l
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	-	-	-



Building together

REVESTIDAN SATE ACRILICO

Version: 2	Revision: 23/12/2024	Previous revision: 18/07/2022	Date of printing: 23/12/2024
2-octyl-2H-isothiazol-3-one Diuron (ISO)	0.0022 0.00032	0.00022 0	0.000122 0.00022
- WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER: Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1) 2-octyl-2H-isothiazol-3-one Diuron (ISO)	<u>PNEC STP</u> mg/l - s/r 58	<u>PNEC Sediments</u> mg/kg dw/d - 0.0475 0.05172	<u>PNEC Sediments</u> mg/kg dw/d - 0.00475 0.005172
- PREDICTED NO-EFFECT CONCENTRATION, TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans: Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1) 2-octyl-2H-isothiazol-3-one Diuron (ISO)	<u>PNEC Air</u> mg/m3 - s/r -	<u>PNEC Soil</u> mg/kg dw/d - 0.0082 0.012	<u>PNEC Oral</u> mg/kg dw/d - n/b n/b
(-) - PNEC not available (without data of registration REACH). n/b - PNEC not derived (not bioaccumulative potential). s/r - PNEC not derived (not identified hazard).			

8.2

EXPOSURE CONTROLS:

ENGINEERING MEASURES:



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:
Avoid the inhalation of vapours.

- Protection of eyes and face:
It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:
It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:
As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:	No.
Safety goggles:	Advisable.
Face shield:	No.
Gloves:	Advisable. Use suitable protective rubber or PVC gloves (EN374), when the product is handled for prolonged periods.
Boots:	No.
Apron:	No.
Clothing:	No.

- Thermal hazards:
Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:
Avoid any spillage in the environment. Avoid any release into the atmosphere.

- Spills on the soil:
Prevent contamination of soil.

- Spills in water:
Do not allow to escape into drains, sewers or water courses.

-Water Management Act:



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

This product contains the following substances included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU:
Diuron (ISO).

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use*):

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory c) Coating for exterior walls of mineral substrate, water-borne. VOC (product ready for use*): (REVESTIDAN SATE ACRILICO Cod. 720001 = 100 in volume): 17,8 g/l* (VOC max.40 g/l* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 0,00 % Weight, VOC (supply): 1,00 % Weight, VOC: 0,00 % C (expressed as carbon), Molecular weight (average): 0,00 , Number C atoms (average)Not applicable.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:
-----	--

Appearance

Physical state:	Liquid Viscous
Colour:	Diverse
Odour:	Odourless
Odour threshold:	Not available (mixture).

Change of state

Freezing point:	Not available (mixture).
Initial boiling point:	107 °C at 760 mmHg

- Flammability:

Flashpoint:	Not flammable
Lower/upper flammability or explosive limits:	Not available
Autoignition temperature:	275 °C

Stability

Decomposition temperature: Not applicable (thermally stable).

pH-value

pH: 8 at 20°C

- Viscosity:

Dynamic viscosity:	Not available.
Kinematic viscosity:	Higher than 20.5 mm2/s at 40°C

- Solubility(ies):

Solubility in water	Miscible
Liposolubility:	Not applicable (inorganic product).
Partition coefficient: n-octanol/water:	Not applicable (inorganic product).

- Volatility:

Vapour pressure:	17,535* mmHg at 20°C
Vapour pressure:	12,03 kPa at 50°C
Evaporation rate:	Not available (lack of data).

Density

Relative density:	1,840 ± 0,12 at 20/4°C	Relative water
Relative vapour density:	< 1 (lighter than air).	

Particle characteristics

Particle size:	Not applicable.
----------------	-----------------

- Explosive properties:

Not available.

- Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2	OTHER INFORMATION:
-----	--------------------

Information regarding physical hazard classes

No additional information available.

Other security features:

Surface tension:	72,8* din/cm at 20°C
Heat of combustion:	67 Kcal/kg
VOC (supply):	1,0 ± 0,03 % Weight
VOC (supply):	17,8 g/l
Nonvolatile:	3,09 * % Weight

1h. 60°C



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10: STABILITY AND REACTIVITY

10.1	REACTIVITY:
------	-------------

- Corrosivity to metals:

It is not corrosive to metals.

- Pyrophorical properties:

It is not pyrophoric.

10.2	CHEMICAL STABILITY:
------	---------------------

Stable under recommended storage and handling conditions.

10.3	POSSIBILITY OF HAZARDOUS REACTIONS:
------	-------------------------------------

Possible dangerous reaction with oxidizing agents, acids, alkalis, reducing agents.

10.4	CONDITIONS TO AVOID:
------	----------------------

- Heat:

Keep away from sources of heat.

- Light:

Not applicable.

- Air:

The product is not affected by exposure to air, but should not be left the containers open.

- Pressure:

Not relevant.

- Shock:

The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

10.5	INCOMPATIBLE MATERIALS:
------	-------------------------

Keep away from oxidizing agents, acids, alkalis, reducing agents.

10.6	HAZARDOUS DECOMPOSITION PRODUCTS:
------	-----------------------------------

As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides, Hydrocyanic acid, halogenated compounds, sulfur oxides, hydrochloric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2022/692 (CLP).

11.1	INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :
------	--

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m3·4h Inhalation
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9 Rat	140 Rat	> 1230 Rat
2-octyl-2H-isothiazol-3-one	125 Rat	311 Rabbit	> 270 Rat
Diuron (ISO)	4150 Rat	> 5000 Rat	> 5000 Rat
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m3·4h Inhalation
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9	140	> 50
2-octyl-2H-isothiazol-3-one	125	*311	270
Diuron (ISO)	*> 500	-	-

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

- No observed adverse effect level

Not available

- Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
--------------------	----------------	------	------------------------------------	----------



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Not classified as a dangerous product for target organs.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

- Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:Routes of exposure

Not available.

- Short-term exposure:

Not available.

danosa Building together	REVESTIDAN SATE ACRILICO	
--	--------------------------	--

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

	- <u>Long-term or repeated exposure:</u> Not available. <u>INTERACTIVE EFFECTS:</u> Not available. <u>INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:</u> - <u>Dermal absorption:</u> Not available. - <u>Basic toxicokinetics:</u> Not available. <u>ADDITIONAL INFORMATION:</u> Not available.
11.2	<u>INFORMATION ON OTHER HAZARDS:</u> <u>Endocrine disrupting properties:</u> This product contains, in a concentration equal to or greater than 0.1% by weight, substances that are under evaluation due to their possible endocrine disrupting properties: Diuron (ISO). <u>Other information:</u> No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2022/692 (CLP).

12.1

TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.19 - Fishes	0.16 - Daphniae	0.037 - Algae
2-octyl-2H-isothiazol-3-one	0.12 - Fishes	0.18 - Daphniae	0.15 - Algae
Diuron (ISO)	15 - Fishes	1.4 - Daphniae	0.022 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.02 - Fishes	0.011 - Daphniae	0.004 - Algae
2-octyl-2H-isothiazol-3-one	0.022 - Fishes	0.035 - Daphniae	0.068 - Algae
Diuron (ISO)	0.0012 - Fishes	0.56 - Daphniae	0.0032 - Algae

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	Cat.3	HARMFUL: Harmful to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2

PERSISTENCE AND DEGRADABILITY:
- Biodegradability:
Not available.

Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)		- - 55	Not easy
2-octyl-2H-isothiazol-3-one		- - -	Not easy



Version: 2

SECTION 14: TRANSPORT INFORMATION

14.1	UN NUMBER OR ID NUMBER:
------	-------------------------

14.2	UN PROPER SHIPPING NAME:
------	--------------------------

14.3	<u>TRANSPORT HAZARD CLASS(ES):</u>
------	------------------------------------

14.4	PACKING GROUP:
------	----------------

14.5	<u>ENVIRONMENTAL HAZARDS:</u>
------	-------------------------------

14.6	SPECIAL PRECAUTIONS FOR USER:
------	-------------------------------

14.7	MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:
------	--

SECTION 15: REGULATORY INFORMATION

15.1	SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:
------	---

15.2	CHEMICAL SAFETY ASSESSMENT:
------	-----------------------------



REVESTIDAN SATE ACRILICO

Version: 2

Revision: 23/12/2024

Previous revision: 18/07/2022

Date of printing: 23/12/2024

SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2022/692 (CLP), Annex III:

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Threshold Limit Values, (AGCIH, 2021).
- European agreement on the international carriage of dangerous goods by road, (ADR 2023).
- International Maritime Dangerous Goods Code IMDG including Amendment 41-22 (IMO, 2022).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

HISTORIC: REVISION:

Version: 1 18/07/2022

Version: 2 23/12/2024

Changes since previous Safety Data Sheet:

Changes that have been introduced with respect to the previous version due to the structural and content adaptation of the Safety Data Sheet to Regulation (EU) No. 2020/878: All sections.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.

Safety Data Sheet (SDS) generated with the 6.0.0.185 version of the JMTCHEM software (www.jmtchemsolutions.com).