

tesa® Professional 4325

product information



General purpose paper masking tape

tesa® 4325 is a finely creped paper masking tape with a natural rubber adhesive

Main Application

- Indoor applications
- General purpose applications
- Masking during paintwork
- Fixing masking materials
- Sealing, packaging, bundling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

- | | | | |
|--------------------|-----------------------|-----------------------|---------|
| • Backing material | slightly-creped paper | • Elongation at break | 10 % |
| • Total thickness | 120 µm | • Tensile strength | 33 N/cm |
| • Type of adhesive | natural rubber | | |

Adhesion to

- | | |
|---------|----------|
| • steel | 2.6 N/cm |
|---------|----------|

Properties

- | | | | |
|--------------------|------|---------------------|-----|
| • Hand tearability | ●●●● | • Sharp colour edge | ●●● |
| • Paint anchorage | ●●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04325>