

Test Conducted: Based on **BS EN 1078:2012+A1:2012**

Helmets for pedal cyclists and for users of skateboards and roller skates

Test Results: Details shown as following table

Clause	Test Method/Requirement	Result
4.1	<p>Materials</p> <p>For those parts of the helmet coming into contact with the skin, the material used should be known not to undergo appreciable alteration from contact with sweat or with substances likely to be found in toiletries.</p> <p>Materials shall not be used which are known to cause skin disorders.</p>	N/T
4.2	<p>Construction</p> <p>The helmet normally consists of a means of absorbing impact energy and means of retaining the helmet on the head in an accident.</p> <p>The helmet should be durable and withstand handling. The helmet shall be so designed and shaped that parts of it (visor, rivets, ventilators, edges, fastening device and the like) are not likely to injure the user in normal use.</p> <p><i>NOTE: Helmets should:</i> <i>have low weight;</i> <i>be ventilating;</i> <i>be easy to put on and take off;</i> <i>be usable with spectacles;</i> <i>not significantly interfere with the ability of the user to hear traffic noise.</i></p>	Pass See annex 1
4.3	<p>Field of vision</p> <p>When tested in accordance with 5.7 there shall be no occultation in the field of vision bounded by angles as follows (see Figure 1):</p> <ul style="list-style-type: none"> - horizontally: min. 105° from the longitudinal vertical median plane to the left and right hand sides; - upwards: min. 25° from the reference plane; - downwards: min. 45° from the basic plane. 	Pass See annex 4
4.4	<p>Shock absorbing capacity</p> <p>The helmet shall give protection to the forehead, rear, sides, temples and crown of the head.</p> <p>When tested in accordance with 5.3 and 5.4 the peak acceleration shall not, for each impact, exceed 250 g for the velocity of 5,42 +0.1,-0 m/s on the flat anvil, and 4,57+0.1,-0 m/s on the kerbstone anvil.</p> <p><i>NOTE: These are theoretically equivalent to 1 497 mm and 1 064 mm drop heights respectively.</i></p>	Pass See annex 2
4.5	<p>Durability</p> <p>After being tested the helmet shall not exhibit damage that could cause significant injury to the wearer (sharp edges, points).</p>	Pass
4.6	<p>Retention system</p>	
4.6.1	<p>General</p> <p>Means shall be provided for retaining the helmet on the wearer's head. All parts of the retention system shall be securely attached to the helmet.</p>	Pass



4.6.2	<p>Chin strap The chin strap shall not include a chin cup. Any chin strap shall be no less than 15 mm wide. Chin straps may be fitted with means of enhancing comfort for the wearer.</p>	Pass
4.6.3	<p>Fastening device Any retention system shall be fitted with a device to adjust and maintain tension in the system. The device shall be capable of adjustment so that the buckle does not sit on the jaw bone.</p>	Pass
4.6.4	<p>Color No part of the retention system shall be colored green. <i>NOTE: It is recommended that the opening mechanism be marked with red or orange color.</i></p>	Pass
4.6.5	<p>Strength When tested in accordance with 5.5, the dynamic extension of the retention system shall not exceed 35 mm and the residual extension shall not exceed 25 mm. For this purpose, extension includes slippage of the fastening device. Damage to the retention system shall be accepted provided that the above requirements are met. <i>NOTE: In this test, slippage of the fastening device can be measured and recorded separately from other contributions to the extension but this is for information only and is not subject to a separate requirement.</i></p>	Pass See annex 3
4.6.6	<p>Effectiveness When tested in accordance with 5.6 the helmet shall not come off the headform.</p>	Pass
4.6.7	<p>Ease of release Following the strength test in accordance with 5.5 and with the load still applied, it shall be possible to open the release system with one hand.</p>	Pass
5.2	<p>Inspection and determination of mass Inspect the helmet to ascertain whether it is suitable for its intended purpose and fulfils the general requirements in 4.2. Determine the mass of the helmets of the same size submitted for testing. Calculate and record the mean value in g rounded off to the nearest 10 g, stating the size of the helmet.</p>	Pass See annex 1
6	<p>Marking Each helmet shall be marked in such a way that the following information is easily legible by the user and is likely to remain legible throughout the life of the helmet:</p> <ul style="list-style-type: none"> a. the number of this European standard; b. the name or trademark of the manufacturer; c. the designation of the model; d. the designation, which shall be one or more of the following:-helmet for pedal cyclists, skateboarders or roller skaters; e. the size or size range of the helmet, quoted as the circumference (in centimeters) of the head which the helmet is intended to fit; f. the weight of the helmet (the average mass in g determined according to EN 1078,5.2); 	N/T



	g. year and quarter of manufacture;	
	h. a label carrying the instructions –“Warning! This helmet should not be used by children while climbing or doing other activities when there is a risk of strangulation/hanging if the child gets trapped with the helmet”	
	In addition, if the helmet has components made of material which are known to be adversely affected by contact with hydrocarbons, cleaning fluids, paints, transfers or other extraneous additions, the helmet shall carry an appropriate warning.	
	If there is a consumer sales packaging, the information specified in a), b), d), and h) shall also be given on that package. The text shall be of minimum font size 12.	
7	Information supplied by the manufacture	N/T
	With every helmet clear information in the language of the country of sale shall be given as follows:	
	a. that the helmet can only protect if it fits well and that the buyer should try different sizes and choose the size which feels secure and comfortable on the head;	
	b. that the helmet should be adjusted to fit the user, e.g. the straps positioned so that they do not cover the ears, the buckle positioned away from the jawbone and the straps and buckle adjusted to be both comfortable and firm;	
	c. how the helmet should be positioned on the head to ensure the intended protection is provide (e.g. that it should be placed so as to protect the forehead and not be pushed too far over the back of the head); to protect the forehead and not be pushed too far over the back of the head);	
	d. that a helmet cannot always protect against injury;	
	e. that a helmet subjected to a severe impact should be discarded and destroyed;	
f. a statement of the danger of modifying or removing any of the original component parts of the helmet other than as recommended by the manufacturer, and that helmets should not be adapted for the purpose of fitting accessories in a way not recommended by the manufacturer.		

Remark:

1. NA = Not applicable.
2. NT = Not tested as per client's request.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8397 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Inspection & Testing Services Co., Ltd. 180 Kazhu Road, Science Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075191 www.sgsgroup.com.cn
 中国·广州·经济技术开发区科学城科珠路180号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075191 e sgs.china@sgs.com

Model: GHM-01

Size: 50-54 cm

Test headform: 535 (EN 960:2006)

Annex-1: Mass

Mass of the samples:

Sample No.	Mass (g)
1	192
2	196
3	194
Average	194

Annex-2: Impact energy attenuation test

Test Specification: BS EN 1078:2012+A1:2012-5.4

Ambient temperature at time of test: 22 °C

Sample No.	Condition	Test Anvil	Test site	Velocity (m/s)	Peak'G	Result
1	High temperature No recondition (Clause 5.4.2.1)	Kerbstone	Right Front	4.57	171.5	Pass
		Flat	Left	5.44	193.1	Pass
2	Low temperature No recondition (Clause 5.4.2.2)	Flat	Crown	5.45	170.3	Pass
		Kerbstone	Left Front	4.60	171.1	Pass
3	Artificial Ageing No recondition (Clause 5.4.2.3)	Kerbstone	Crown	4.59	86.1	Pass
		Flat	Rear	5.49	131.9	Pass

Annex-3: Retention system strength

Test Specification: BS EN 1078:2012+A1:2012-5.5

Ambient temperature at time of test: 22 °C

Sample No.	Condition	Dynamic extension (mm)	Residual extension (mm)	Result
2	Low temperature No recondition (Clause 5.4.2.2)	24.5	6.4	Pass
3	Artificial Ageing No recondition (Clause 5.4.2.3)	22.8	6.8	Pass

Annex-4: Field of vision

Test Specification: BS EN 1078:2012+A1:2012-5.7

Horizontal: >105°

Upward: >25°

Downward: >45°



Test Report

No. GZHL1704012751HM

Date: Apr 26, 2017

Page 6 of 10

Model: GHM-01

Size: 54-58 cm

Test headform: 575 (EN 960:2006)

Annex-1: Mass

Mass of the samples:

Sample No.	Mass (g)
1	219
2	216
3	216
Average	217

Annex-2: Impact energy attenuation test

Test Specification: BS EN 1078:2012+A1:2012-5.4

Ambient temperature at time of test: 22 °C

Sample No.	Condition	Test Anvil	Test site	Velocity (m/s)	Peak'G	Result
1	High temperature No recondition (Clause 5.4.2.1)	Kerbstone	Right Front	4.57	174.1	Pass
		Flat	Left	5.42	161.3	Pass
2	Low temperature No recondition (Clause 5.4.2.2)	Flat	Crown	5.45	184.6	Pass
		Kerbstone	Left Front	4.57	174.9	Pass
3	Artificial Ageing No recondition (Clause 5.4.2.3)	Kerbstone	Crown	4.57	99.2	Pass
		Flat	Rear	5.44	142.4	Pass

Annex-3: Retention system strength

Test Specification: BS EN 1078:2012+A1:2012-5.5

Ambient temperature at time of test: 22 °C

Sample No.	Condition	Dynamic extension (mm)	Residual extension (mm)	Result
2	Low temperature No recondition (Clause 5.4.2.2)	25.4	11.6	Pass
3	Artificial Ageing No recondition (Clause 5.4.2.3)	23.9	9.4	Pass

Annex-4: Field of vision

Test Specification: BS EN 1078:2012+A1:2012-5.7

Horizontal: >105°

Upward: >25°

Downward: >45°



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8397 1443, or email: CN.Doccheck@sgs.com

180 Kazhu Road, Science Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075191 www.sgs.com.cn
 中国·广州·经济技术开发区科学城科珠路180号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075191 e sgs.china@sgs.com

Sample Photo(s):

<p>Front view</p>	
<p>Side view</p>	



<p>Back view</p>	
<p>Top view</p>	



<p>Bottom view</p>	
<p>Test line for (535) EN 960:2006 head form</p>	



Test line for (575)
EN 960:2006 head
form



End of Report

