



QUICK-CONNECT NOZZLE

Quick-connect nozzle.

- Universal connector, compatible with hose quick couplings.
- European Brass, DW (4MS) quality for use in drinking water installations, on metal models.



TECHNICAL SHEET QUICK-CONNECT NOZZLE

PRODUCT DESCRIPTION

Nozzles for the GARDEN family taps with quick connection for plumbing installations, where the connection is made by threaded ends.

The quick connection makes it easy to install hoses.


PRODUCT SCOPE

Specially designed for outdoor plumbing installations such as gardens, terraces, yards... or in indoor installations where a service tap with a quick connection for hoses, guns, lances and other accessories is required.

GENERAL DIMENSIONS, PRESSURE AND TEMPERATURE


KNURLED NOZZLE METAL QUICK CONNECTION

Code	Size	A (mm)	B (mm)
08407	3/4M	29	35
08407U	3/4M	29	35




HEXAGONAL NOZZLE METAL QUICK CONNECTION

Code	Size	A E/A (mm)	A E/C (mm)	B (mm)
08406	1/2M	26	25	33



PLASTIC QUICK-CONNECT NOZZLE

Code	Size	A (mm)	B (mm)
08408	3/4M	34	39
08409	1/2M	27	39






MATERIALS


Metal quick-connect nozzle models

Item	Component	Material	Finishing
1	O-ring	NBR	-
2	Nozzle	Brass CW617N	Chrome plated
3	Flat joint	EPDM	-



Plastic quick-connect nozzle models

Item	Component	Material	Finishing
1	O-ring	NBR	-
2	Nozzle	PP	Black
3	Flat joint	EPDM	-



Compatibility with fluids

Fluid	Compatibility
Drinking water	Excellent

For any other fluid, please contact Arco technical service.

Excluding freezing.

INSTALLATION AND OPERATION INSTRUCTIONS

Before performing any action, the water supply to the installation should be shut off. Make sure there is no dirt or foreign objects in the connection to the accessory.

Do not alter the assembly of the tap components; replacement or disassembly of them may cause external leaks or vary their operation.



All products have an environmental impact during its life cycle, even once retired. All the components of this product can be recycled. Once the use is over, leave the valve in any recycling green point. Válvulas Arco reserves the right to change the product or any of its technical specifications without prior notice.

FT04070ING – Edition 2024-12