

PRODUCT CERTIFICATE

MIM 104 - FARM IMPLEMENT

Description MIM 104 FARM IMPLEMENT has been designed for field and road transport with implements machinery and trailers. MIM 104 is a high-speed tyre, which optimizes travel times. MRL tread design ensures a long service life also in harsh conditions and is stubble in the fields.



Construction **Bias**
Tyre size **11L-15 SL**

Application



Trailer



Baler

Version	International Standard
RIM	8LB
OD (mm)	777
SW (mm)	279
SLR (mm)	342
RC (mm)	2300
NSD (mm)	8.0
TRA Code	I-1

Special Characteristics



Version	US Standard
RIM	8LB
OD (inch)	30.6
SW (inch)	10.98
SLR (inch)	13.46
RC (inch)	90.55
NSD (32 nd)	10.08
TRA Code	I-1

For MRL Tyres Ltd

[Signature]



Chief Technology Officer



PRODUCT CERTIFICATE

MIM 104 - FARM IMPLEMENT

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX / SPEED SYMBOL	Inflated Pressure (bar)	Recommend load, kg				Weight
							(International standard)Speed, km/h				
							Mixed application				
							25	30	40	50	kg
11L-15 SL	E9*106R00/19*6507*00	MRL02508026TL	TL	08	113A8/B	1.9	1130	1100	980	882	17.51
						2.1	1200	1170	1040	936	
						2.3	1270	1240	1100	990	
						2.5	1320	1290	1150	1150	
11L-15 SL	-	MRL02510026TT	TT	10	118A8/B	2.4	1330	1310	1160	1044	17.51
						2.6	1400	1370	1220	1098	
						2.8	1460	1430	1270	1143	
						3.0	1520	1490	1320	1320	
11L-15 SL	E11 106R 001836	MRL02512026TT	TT	12	121A8/B	3.0	1500	1460	1300	1170	16.75
						3.2	1550	1520	1350	1215	
						3.4	1610	1580	1400	1260	
						3.6	1670	1630	1450	1450	
11L-15 SL	E11 106R 001836	MRL02512026TL	TL	12	121A8/B	3.0	1500	1460	1300	1170	17.64
						3.2	1550	1520	1350	1215	
						3.4	1610	1580	1400	1260	
						3.6	1670	1630	1450	1450	
11L-15 SL	E9*106R00/19*6502*00	MRL02516026TL	TL	16	125A8/B	4.1	1760	1720	1530	1377	20.62
						4.3	1810	1770	1570	1413	
						4.5	1850	1810	1610	1449	
						4.7	1900	1860	1650	1650	

For MRL Tyres Ltd

(Signature)



Chief Technology Officer



PRODUCT CERTIFICATE

MIM 104 - FARM IMPLEMENT

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX / SPEED SYMBOL	Inflated Pressure (psi)	Recommend load, lbs				Weight
							(US standard) Speed, mph				
							Mixed application				
							16	19	25	31	lbs
11L-15 SL	E9*106R00/19*6507*00	MRL02508026TL	TL	08	113A8/B	28	2486	2420	2156	1940	38.6
						30	2640	2574	2288	2059	
						33	2794	2728	2420	2178	
						36	2904	2838	2530	2530	
11L-15 SL	-	MRL02510026TT	TT	10	118A8/B	35	2926	2882	2552	2297	38.6
						38	3080	3014	2684	2416	
						41	3212	3146	2794	2515	
						44	3344	3278	2904	2904	
11L-15 SL	E11 106R 001836	MRL02512026TT	TT	12	121A8/B	44	3300	3212	2860	2574	37.0
						46	3410	3344	2970	2673	
						49	3542	3476	3080	2772	
						52	3674	3586	3190	3190	
11L-15 SL	E11 106R 001836	MRL02512026TL	TL	12	121A8/B	44	3300	3212	2860	2574	38.9
						46	3410	3344	2970	2673	
						49	3542	3476	3080	2772	
						52	3674	3586	3190	3190	
11L-15 SL	E9*106R00/19*6502*00	MRL02516026TL	TL	16	125A8/B	59	3872	3784	3366	3029	45.5
						62	3982	3894	3454	3109	
						65	4070	3982	3542	3188	
						68	4180	4092	3630	3630	

For MRL Tyres Ltd

(Signature)



Chief Technology Officer

Disclaimer: All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. MRL Tyres Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication, certificates or the website are the exclusive property of MRL Tyres Ltd. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by MRL Tyres Ltd.