

PRODUCT CERTIFICATE

MIM 104 - FARM IMPLEMENT

Description

MIM 104 FARM IMPLEMENT has been designed for field and road transport with implements machinery and trailers. MIM 104 is a high-speed tyre, which optimizes travel times. MRL tread design ensures a long service life also in harsh conditions and is stubble in the fields.

Construction

Tyre size

Bias

31x13.50-15 SL

Application



Trailer



Baler



| Version | International Standard |
|----------|------------------------|
| RIM | 10LB |
| OD (mm) | 782 |
| SW (mm) | 351 |
| SLR (mm) | 356 |
| RC (mm) | 2339 |
| NSD (mm) | 9.5 |
| TRA Code | I-1 |

Special Characteristics



| Version | US Standard |
|-------------|-------------|
| RIM | 10LB |
| OD (inch) | 30.78 |
| SW (inch) | 13.82 |
| SLR (inch) | 14.02 |
| RC (inch) | 92.09 |
| NSD (32 nd) | 11.96 |
| TRA Code | I-1 |

For MRL Tyres Ltd




Chief Technology Officer



PRODUCT CERTIFICATE

MIM 104 - FARM IMPLEMENT

| SIZE | ECE | SAP CODE | TYPE | PR | LOAD INDEX / SPEED SYMBOL | Inflated Pressure (bar) | Recommend load, kg | | | | Weight |
|------------|----------------------|---------------|------|----|---------------------------|-------------------------|-------------------------------------|------|------|------|--------|
| | | | | | | | (International standard)Speed, km/h | | | | |
| | | | | | | | Mixed Application | | | | |
| | | | | | | | 25 | 30 | 40 | 50 | kg |
| 31x13.5-15 | E9*106R00/15*1730*00 | MRL14708026TL | TL | 08 | 114 B | 2.4 | 1300 | 1270 | 1130 | 1017 | 26.9 |
| | | | | | | 2.6 | 1360 | 1330 | 1180 | 1062 | |
| | | | | | | 2.8 | 1410 | 1380 | 1230 | 1107 | |
| | | | | | | 3.1 | 1510 | 1470 | 1310 | 1180 | |
| 31x13.5-15 | E9*106R00/15*1714*00 | MRL14712026TL | TL | 12 | 124 B | 3.9 | 1730 | 1690 | 1500 | 1350 | 27.1 |
| | | | | | | 4.3 | 1830 | 1790 | 1590 | 1431 | |
| | | | | | | 4.7 | 1930 | 1890 | 1680 | 1512 | |
| | | | | | | 5.2 | 2050 | 2000 | 1780 | 1600 | |

| SIZE | ECE | SAP CODE | TYPE | PR | LOAD INDEX / SPEED SYMBOL | Inflated Pressure (psi) | Recommend load, lbs | | | | Weight |
|------------|----------------------|---------------|------|----|---------------------------|-------------------------|--------------------------|------|------|------|--------|
| | | | | | | | (US standard) Speed, mph | | | | |
| | | | | | | | Mixed Application | | | | |
| | | | | | | | 16 | 19 | 25 | 31 | lbs |
| 31x13.5-15 | E9*106R00/15*1730*00 | MRL14708026TL | TL | 08 | 114 B | 35 | 2860 | 2794 | 2486 | 2237 | 59.3 |
| | | | | | | 38 | 2992 | 2926 | 2596 | 2336 | |
| | | | | | | 41 | 3102 | 3036 | 2706 | 2435 | |
| | | | | | | 45 | 3322 | 3234 | 2882 | 2596 | |
| 31x13.5-15 | E9*106R00/15*1714*00 | MRL14712026TL | TL | 12 | 124 B | 57 | 3806 | 3718 | 3300 | 2970 | 59.8 |
| | | | | | | 62 | 4026 | 3938 | 3498 | 3148 | |
| | | | | | | 68 | 4246 | 4158 | 3696 | 3326 | |
| | | | | | | 75 | 4510 | 4400 | 3916 | 3520 | |

For MRL Tyres Ltd

(Signature)



Chief Technology Officer

Disclaimer: All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. MRL Tyres Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication, certificates or the website are the exclusive property of MRL Tyres Ltd. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by MRL Tyres Ltd.