

PRODUCT CERTIFICATE

RRT 770 - FARM MAXX



Description RRT 770 FARM MAXX is a wide contact patch radial tire developed for modern and high-power tractors for several heavy-duty applications such as soil tillage, field and road transport, and vineyard harvesting. MRL provides special self-cleaning deep lugs tread pattern, radial nylon casing, mudguard, and unique shoulder design to ensure excellent grip and extended tyre life cycle.

Construction Radial
Tyre size 280/70 R16

Application



Version	International Standard
RIM	W8L
OD (mm)	798
SW (mm)	282
SLR (mm)	368.7
RC (mm)	2391.7
NSD (mm)	32
TRA Code	R-1W

Special Characteristics



Version	US Standard
RIM	W8L
OD (inch)	31.42
SW (inch)	11.1
SLR (inch)	14.5
RC (inch)	94.2
NSD (32 nd)	40.3
TRA Code	R-1W

For MRL Tyres Ltd


Chief Technology Officer





PRODUCT CERTIFICATE

RRT 770 - FARM MAXX

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX/ SPEED SYMBOL	Inflation Pressure	Recommended load, kg								WEIGHT	
							(International Standard)Speed, km/h									
							Field operation		Road Operation; Not high and Sustained Torque							
							High Torque	Low Torque								
							bar	10	10	Static	10	20	30	40	50	(KG)
280/70R16	E9*106R00/16*1999*00	MRL32400133TL	TL	-	112A8/B	1.2	840	970	1880	1220	1000	810	760	760	25.912	
						1.5	950	1100	2130	1390	1140	920	860	860		
						1.9	1080	1250	2420	1580	1300	1050	980	980		
						2.4	1230	1430	2760	1800	1480	1200	1120	1120		

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX/ SPEED SYMBOL	Inflation Pressure	Recommended load, lbs								WEIGHT
							(US Standard)Speed, mph								
							Field operation		Road Operation; Not high and Sustained Torque						
							High Torque	Low Torque							
						psi	6	6	Static	6	16	20	25	31	(LBS)
280/70R16	E9*106R00/16*1999*00	MRL32400133TL	TL	-	112A8/B	18	1850	2140	4140	2690	2200	1780	1670	1670	57.152
						22	2090	2420	4690	3060	2510	2030	1890	1890	
						28	2380	2750	5330	3480	2860	2310	2160	2160	
						35	2710	3150	6080	3960	3260	2640	2470	2470	

For MRL Tyres Ltd



Chief Technology Officer

Disclaimer: All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. MRL Tyres Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication, certificates or the website are the exclusive property of MRL Tyres Ltd. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by MRL Tyres Ltd.



PRODUCT CERTIFICATE

RRT 770 - FARM MAXX

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX/ SPEED SYMBOL	Inflation Pressure	Recommended load, kg									WEIGHT
							(International Standard)Speed, km/h									
							Field operation		Road Operation; Not high and Sustained Torque							
							High Torque	Low Torque								
						bar	10	10	Static	10	20	30	40	65	(KG)	
280/70R16	E9*106R00/20*6669*00	MRL47200133TL	TL	-	112D/115A8	1.2	910	1060	2040	1340	1090	890	830	760	25.912	
						1.5	1030	1200	2320	1520	1240	1010	940	860		
						1.9	1170	1370	2640	1730	1410	1150	1070	980		
						2.4	1330	1560	3010	1970	1610	1310	1215	1120		

Size	ECE	SAP CODE	TYPE	PR	LOAD INDEX/ SPEED SYMBOL	Inflation Pressure	Recommended load, lbs									WEIGHT
							(US Standard)Speed, mph									
							Field operation		Road Operation; Not high and Sustained Torque							
							High Torque	Low Torque								
						psi	6	6	Static	6	16	20	25	40	(LBS)	
280/70R16	E9*106R00/20*6669*00	MRL47200133TL	TL	-	112D/115A8	18	2000	2330	4490	2950	2400	1960	1830	1670	57.152	
						22	2270	2640	5110	3350	2730	2220	2070	1890		
						28	2580	3020	5810	3810	3110	2530	2360	2160		
						35	2930	3440	6630	4340	3550	2890	2680	2470		

For MRL Tyres Ltd

(Signature)



Chief Technology Officer

Disclaimer: All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. MRL Tyres Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication, certificates or the website are the exclusive property of MRL Tyres Ltd. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by MRL Tyres Ltd.