

PRODUCT CERTIFICATE



Agricultural Tyres

R-1W FARM SUPER 85 RRT 885

FARM SUPER RRT 885 is mainly for soil tillage and both field and road transport as well as for spreading operations. Extra reinforced carcass and cut resistance compound provide extended life. MRL special tread design allows for carrying very heavy loads at low pressure and ensuring reduced soil compaction.



UTILITY TRACTOR MFWA



COMBINE HARVESTER



AGRICULTURAL LOADER



4WD TRACTOR



2WD TRACTOR

Salient Features

Feature	Advantage	Benefit
Strong casing	Higher load carrying capacity	Extended Life
Heat resistance compound	Lower rolling resistance	Better mileage and durability
Cut and Chip resistance compound	Resistance to wear and tear	Support smooth operations

Technical Data

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs							
				Speed, mph													
				Field operation						Road Operation; Not high and Sustained Torque							
																High Torque	Low Torque
				SW	OD					in	in	in	in	PSI	6	6	static
340/85R24	TL	W12	W11	13.7	46.9	21.4	140.1	125A8/B	12	2670	3080	5620	3680	2710	2620	2440	2440
									15	3040	3520	6390	4160	3080	2970	2780	2780
									17.4	3370	3920	7090	4630	3410	3300	3080	3080
									20	3680	4300	7750	5070	3740	3610	3370	3370
									23.2	3990	4650	8370	5460	4030	3900	3630	3630

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs								
										Speed, mph								
				SW	OD					Field operation		Road Operation; Not high and Sustained Torque						
										High Torque	Low Torque							
										in	in	in	in	PSI	6	6	static	6
340/85R24	TL	W12	W11	13.7	46.9	21.4	140.1	125D/128A8	12	2910	3390	5620	3680	2910	2690	2580	2440	
									15	3300	3880	6390	4160	3280	3040	2910	2780	
									17.4	3680	4320	7090	4630	3660	3370	3240	3080	
									20	4030	4740	7750	5070	3990	3700	3550	3370	
									23.2	4360	5110	8370	5460	4320	3990	3810	3630	