

PRODUCT CERTIFICATE



Agricultural Tyres

R-1W FARM SUPER 85 RRT 885

FARM SUPER RRT 885 is mainly for soil tillage and both field and road transport as well as for spreading operations. Extra reinforced carcass and cut resistance compound provide extended life. MRL special tread design allows for carrying very heavy loads at low pressure and ensuring reduced soil compaction.



UTILITY TRACTOR MFWA



COMBINE HARVESTER



AGRICULTURAL LOADER



4WD TRACTOR



2WD TRACTOR

Salient Features

Feature	Advantage	Benefit
Strong casing	Higher load carrying capacity	Extended Life
Heat resistance compound	Lower rolling resistance	Better mileage and durability
Cut and Chip resistance compound	Resistance to wear and tear	Support smooth operations

Technical Data

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs							
				Speed, mph													
										Field operation		Road Operation; Not high and Sustained Torque					
										High Torque	Low Torque						
				SW	OD					in	in	in	in	PSI	6	6	static
380/85R24	TL	W12	W11,W13	15.0	49.4	22.5	147.9	131A8/B	12	3150	3680	6540	4270	3150	3040	2840	2840
									15	3590	4190	7440	4870	3590	3460	3240	3240
									17.4	3990	4650	8300	5420	4010	3850	3610	3610
									20	4360	5090	9120	5950	4410	4250	3960	3960
									23.2	4710	5510	9890	6450	4760	4600	4300	4300

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs							
				Speed, mph													
										Field operation		Road Operation; Not high and Sustaind Torque					
										High Torque	Low Torque						
				SW	OD					in	in	in	in	PSI	6	6	static
380/85R24	TL	W12	W11,W13	15.0	49.4	22.5	147.9	131D/134A8	12	3410	4030	6540	4270	3370	3110	2970	2840
									15	3900	4580	7440	4870	3830	3550	3390	3240
									17.4	4340	5090	8300	5420	4270	3960	3790	3610
									20	4760	5570	9120	5950	4690	4340	4160	3960
									23.2	5150	6040	9890	6450	5090	4710	4520	4300