

PRODUCT CERTIFICATE



Agricultural Tyres

AW/I-1 IMPLEMENT MAW 200

MAW 200 is a tire designed for implement machinery & trailers in soil tillage, grassland, and haulage applications. More land helps for more mileage and life. Strong casing construction ensures optimum durability in defined applications.



BALER



AGRICULTURAL
IMPLEMENTS



TRAILER

Salient Features

Feature	Advantage	Benefit
Increased contact patch	Additional rubber in the tread area	Extended mileage & life
Wider tread pattern	Extended footprint	Lessen soil degradation
Strong nylon casing	Higher strength	More durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed / Symbol	Inflation Pressure	Recommended Load, kgs.										
				SW mm	OD mm						Speed, km/h										
											Free Rolling Application					Drive Wheel Application					
											Bar	Static	10	25	30	40	Static	10	25	30	40
10.0/75-15.3	TL	9	-	264	760	343	2227	10	123A6/119A8		3.4	2130	1660	1380	1290	1160	2310	1260	1050	980	890
											3.8	2270	1770	1470	1370	1230	2390	1310	1090	1010	920
											4.2	2410	1880	1560	1460	1310	2480	1360	1130	1050	950
											4.7	2560	2000	1660	1550	1390	2570	1410	1170	1090	980

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.										
				SW	OD						Speed, km/h										
											Free Rolling Application					Drive Wheel Application					
											mm	mm	mm	mm	mm	Bar	Static	10	25	30	40
10.0/75-15.3	TL	9	-	264	760	343	2227	12	126A6/122A8		4.1	2330	1830	1510	1420	1270	2510	1390	1160	1070	960
											4.5	2480	1950	1610	1510	1350	2600	1440	1200	1110	1000
											5.0	2640	2070	1710	1600	1440	2700	1490	1240	1150	1030
											5.6	2810	2200	1820	1700	1530	2800	1540	1280	1190	1070

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				SW	OD						Speed, km/h									
											Free Rolling Application					Drive Wheel Application				
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TT	9	-	264	760	343	2227	12	126A6/122A8	4.1	2330	1830	1510	1420	1270	2510	1390	1160	1070	960
										4.5	2480	1950	1610	1510	1350	2600	1440	1200	1110	1000
										5.0	2640	2070	1710	1600	1440	2700	1490	1240	1150	1030
										5.6	2810	2200	1820	1700	1530	2800	1540	1280	1190	1070

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				SW	OD						Speed, km/h									
											Free Rolling Application					Drive Wheel Application				
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TL	9	-	264	760	343	2227	14	130A6/126A8	Bar	Static	10	25	30	40	Static	10	25	30	40
										4.8	2610	2040	1700	1580	1420	2810	1540	1280	1190	1080
										5.4	2770	2170	1810	1680	1510	2910	1600	1330	1230	1120
										5.9	2950	2310	1920	1790	1610	3020	1660	1380	1280	1160
										6.6	3140	2460	2040	1900	1710	3130	1720	1430	1330	1200

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				SW	OD						Speed, km/h									
											Free Rolling Application					Drive Wheel Application				
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TT	9	-	264	760	343	2227	14	130A6/126A8	Bar	Static	10	25	30	40	Static	10	25	30	40
										4.8	2610	2040	1700	1580	1420	2810	1540	1280	1190	1080
										5.4	2770	2170	1810	1680	1510	2910	1600	1330	1230	1120
										5.9	2950	2310	1920	1790	1610	3020	1660	1380	1280	1160
										6.6	3140	2460	2040	1900	1710	3130	1720	1430	1330	1200

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				SW	OD						Speed, km/h									
											Free Rolling Application					Drive Wheel Application				
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TL	9	-	264	760	343	2227	16	134A6/130A8	Bar	Static	10	25	30	40	Static	10	25	30	40
										5.7	2910	2290	1880	1760	1580	3150	1730	1430	1340	1200
										6.3	3090	2430	2000	1870	1680	3270	1790	1480	1390	1240
										7.0	3290	2580	2130	1990	1790	3390	1860	1540	1440	1290
										7.8	3500	2740	2270	2120	1900	3510	1930	1600	1490	1340

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				SW	OD						Speed, km/h									
											Free Rolling Application					Drive Wheel Application				
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TT	9	-	264	760	343	2227	16	134A6/130A8	Bar	Static	10	25	30	40	Static	10	25	30	40
										5.7	2910	2290	1880	1760	1580	3150	1730	1430	1340	1200
										6.3	3090	2430	2000	1870	1680	3270	1790	1480	1390	1240
										7.0	3290	2580	2130	1990	1790	3390	1860	1540	1440	1290
										7.8	3500	2740	2270	2120	1900	3510	1930	1600	1490	1340

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.									
				Speed, km/h																
				Free Rolling Application							Drive Wheel Application									
				SW	OD								Static	10	25	30	40			
		mm	mm	mm	mm			Bar	Static	10	25	30	40	Static	10	25	30	40		
10.0/75-15.3	TL	9	-	264	760	343	2227	18	138A6/134A8	5.7	3240	2540	2110	1970	1760	3510	1930	1600	1490	1340
										6.3	3450	2700	2240	2090	1870	3640	2000	1660	1540	1390
										7.0	3670	2870	2380	2220	1990	3770	2070	1720	1600	1440
										7.8	3900	3050	2530	2360	2120	3910	2150	1780	1660	1490

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.										
				SW	OD						Speed, km/h										
											Free Rolling Application					Drive Wheel Application					
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TT	9	-	264	760	343	2227	18	138A6/134A8		Bar	Static	10	25	30	40	Static	10	25	30	40
											5.7	3240	2540	2110	1970	1760	3510	1930	1600	1490	1340
											6.3	3450	2700	2240	2090	1870	3640	2000	1660	1540	1390
											7.0	3670	2870	2380	2220	1990	3770	2070	1720	1600	1440
											7.8	3900	3050	2530	2360	2120	3910	2150	1780	1660	1490

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs.										
				SW	OD						Speed, km/h										
											Free Rolling Application					Drive Wheel Application					
											mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
10.0/75-15.3	TL	9	-	264	760	343	2227	22	142A6/138A8	Bar	Static	10	25	30	40	Static	10	25	30	40	
											6.2	3650	2850	2360	2200	1990	3940	2150	1790	1670	1500
											6.9	3880	3030	2510	2340	2110	4080	2230	1860	1730	1550
											7.7	4120	3220	2670	2490	2240	4230	2310	1930	1790	1610
											8.5	4380	3420	2840	2650	2380	4380	2400	2000	1860	1670