

PRODUCT CERTIFICATE



Agricultural Tyres

R-1 KIRTI MRT 329

MRT 329 is best suitable for tractors in soil tillage, and spraying applications. Some sizes are suitable for excavators, trailers, and also harvesters. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life cycle. Self-cleaning deep lugs are specially designed to provide enough traction and long life under hard-working conditions. Load-carrying capacity is also a key feature.



SPRAYER



UTILITY TRACTOR MFWA



COMBINE HARVESTER



4WD TRACTOR



2WD TRACTOR

Salient Features

Feature	Advantage	Benefit
Wider tread pattern design	Bigger contact patch	Lowers soil damage & increases stability
Double angled curved lug design	Equitable traction	Better grip on wet & dry surfaces
Optimum notch gap	Better way to pass mud	Enhanced self-cleaning

Technical Data

Size	SKU Code	TYPE	Recommended Rim	Alternate Rim	Unloaded		Loaded Static Radius	Rolling Circum	PR	Load Index	Speed Symbol	Infl. press.	Recommended load, (lbs) Speed, (mph)											
					dimension								Field operation				Road Operation: Not high and Sustained Torque							
													High Torque		Low Torque									
					SW	OD							Static		6		12		19		25			
					in	in																	in	in
14.9-24	MRL06008092TT	TT	W13	W11,W12					08	128 A6/124 A8		19	3300	4600	3680	6610	4600	3680	3300	2970				
					15	50	23	146			21	3500	4870	3880	7000	4870	3880	3500	3150					
												23	3720	5180	4140	7440	5180	4140	3720	3350				
													26	3960	5510	4410	7930	5510	4410	3960	3520			

[illegible]

Size	SKU Code	TYPE	Recommended Rim	Alternate Rim	Unloaded		Loaded Static Radius	Rolling Circum	PR	Load Index	Speed Symbol	Infl. press.	Recommended load, (lbs)							
					dimension								Speed, (mph)							
													Field operation				Road Operation: Not high and Sustained Torque			
					High Torque	Low Torque							6	12	19	25				
					SW	OD							in	in	in	in				

14.9-24	MRL06012092TT	TT	W13	W11,W12					12	135 A6/132 A8			28	4010	5570	4450	8020	5570	4450	4010	3610
													31	4250	5900	4710	8500	5900	4710	4250	3830
					15	50	23	146					34	4520	6280	5020	9030	6280	5020	4520	4060
													38	4800	6670	5330	9600	6670	5330	4800	4410

Size	SKU Code	TYPE	Recommended Rim	Alternate Rim	Unloaded		Loaded Static Radius	Rolling Circum	PR	Load Index	Speed Symbol	Infl. press.	Recommended load, (lbs)								
					dimension								Speed, (mph)								
													Field operation		Road Operation: Not high and Sustained Torque						
					SW	OD							High Torque	Low Torque							
					in	in							in	in	psi	6	6	12	Static	6	12
14.9-24	MRL06014092TT	TT	W13	W11,W12					14	138 A6/135 A8			32	4340	6040	4820	8680	6040	4820	4340	3910
													35	4600	6410	5110	9210	6410	5110	4600	4140
					15	50	23	146					39	4890	6810	5420	9780	6810	5420	4890	4400
													44	5200	7220	5770	10400	7220	5770	5200	4800