

PRODUCT CERTIFICATE



Agricultural Tyres

R-1W FARM SUPER 85 RRT 885

FARM SUPER RRT 885 is mainly for soil tillage and both field and road transport as well as for spreading operations. Extra reinforced carcass and cut resistance compound provide extended life. MRL special tread design allows for carrying very heavy loads at low pressure and ensuring reduced soil compaction.



UTILITY TRACTOR MFWA



COMBINE HARVESTER



AGRICULTURAL LOADER



4WD TRACTOR



2WD TRACTOR

Salient Features

Feature	Advantage	Benefit
Strong casing	Higher load carrying capacity	Extended Life
Heat resistance compound	Lower rolling resistance	Better mileage and durability
Cut and Chip resistance compound	Resistance to wear and tear	Support smooth operations

Technical Data

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs							
				Speed, mph													
				Field operation						Road Operation; Not high and Sustained Torque							
																High Torque	Low Torque
				SW	OD					in	in	in	in	PSI	6	6	static
460/85R34	TL	W16L	W14L,W15L	18.3	65.0	29.8	194.5	147A8/B	12	4960	5770	10400	6780	5020	4820	4520	4520
									15	5640	6590	11850	7730	5730	5510	5150	5150
									17.4	6280	7330	13170	8590	6370	6120	5730	5730
									20	6870	8020	14380	9380	6940	6700	6260	6260
									23.2	7420	8680	15570	10150	7510	7250	6770	6770

Size	Type	Rim	Alternate Rim	Unloaded dimension		Static Loaded Radius	Rolling Circumference	Load index /Speed Symbol	Inflation pressure	Recommend load, lbs								
				Speed, mph														
										Field operation		Road Operation; Not high and Sustained Torque						
										High Torque	Low Torque							
				SW	OD					in	in	in	in	PSI	6	6	static	6
460/85R34	TL	W16L	W14L,W15L	18.3	65.0	29.8	194.5	147D/150A8	12	5420	6340	10400	6780	5350	4930	4740	4520	
									15	6170	7220	11850	7730	6100	5640	5420	5150	
									17.4	6870	8040	13170	8590	6780	6280	6010	5730	
									20	7510	8790	14380	9380	7420	6850	6560	6260	
									23.2	8130	9490	15570	10150	8020	7420	7110	6770	

The content in this publication is subject to change without prior notice, including all product data provided. MRL Tyres Ltd. disclaims any liability for unintentional errors and misprints. All materials and content on this website publication are exclusively owned by MRL Tyres Ltd., and reproduction or distribution is prohibited without explicit permission from MRL Tyres Ltd.