

# SDF Brake Fluid

*High Quality mineral brake fluid for SDF equipment*

---

## Applications

- **Agricultural Equipment**  
Suitable for heavy-duty vehicles, including Agriculture Tractors. This product should be used (only) in the (small) brake- or clutch-command systems that call for such a mineral based fluid.

## Specification and Approvals

## Performance Features and Benefits

- **Comprehensive components**  
Specially selected additives impart good anti-wear, excellent shear stability and oxidation resistance.

## Typical Physical Characteristics

Properties			Method	SDF Brake Fluid
Kinematic Viscosity	at 40°C	mm <sup>2</sup> /s	ISO 3104	34.6
Kinematic Viscosity	at 100°C	mm <sup>2</sup> /s	ISO 3104	7.1
Viscosity Index			ISO 2909	174
Density	at 15°C	Kg/m <sup>3</sup>	ISO 12185	874
Pour Point		°C	ISO 3016	-45
Flash Point	(COC)	°C	ISO 2592	180

These characteristics are typical of current production.

## Advice

Advice on applications not covered in this leaflet may be obtained from your SDF Representative.

## Health and Safety

SDF Brake Fluid is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet which can be obtained from your SDF Representative.

## Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.