

DECLARATION OF PERFORMANCE – CPR/038.1

European Construction Products Regulation – CPR 305/2011

1. Name of the product: **REVAT CAL ESTUCO**
2. Type of product: **Coloured rendering mortar (CR)**
3. Intended uses: **For use in walls, ceilings, columns and partitions covered by the scope of EN 998-1 standard**
4. Name and contact address of the manufacturer:
PROPAMSA S.A.U.
Camí Ciments Molins, s/n. 08620 Sant Vicenç dels Horts
www.propamsa.es
5. System of assessment and verification of constancy of performance: **System 4**
6. Notified laboratory:
The manufacturer performed the factory production control (FPC) and initial type testing under system 4.
7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	Class A1	EN 998-1:2010
Capillary water absorption	W0	
Water vapour permeability coefficient (μ)	≤ 25	
Adhesion	$\geq 0,2 \text{ N/mm}^2$ (Tipo B)	
Thermal conductivity (λ_{10} , dry)	$0,50 \pm 0,05 \text{ W/m}\cdot\text{K}$	
Compressive strength	CS I ($0,4\text{--}2,5 \text{ N/mm}^2$)	
Release of dangerous substances	See SDS	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, 01/07/2013

All the information on conditions of use, employment and storage should be consulted in the product datasheet..