



REVAT[®] CAL ESTUCO

FINE LIMESTONE STUCCO WITH FLOATED FINISH

DESCRIPTION

REVAT CAL ESTUCO is a fine mortar based on aerated limestone, selected aggregates, synthetic resins and different additives that provide a protective and decorative building finish.



TECHNICAL DATA

According to EN 998 -1	CR - CSI
Powdered product	
Reaction to fire	Euroclass A1
Paste product	
Mixing water	40 ± 1%
Application temperature	+5°C to +35°C
Pot life	30 minutes
Hardened product	
Compressive strength	0,4 - 2,5 N/mm ²
Capillarity water absorption	W0
Adhesion	≥ 0.30 N/mm ²

APPLICATIONS

Decorative finish, in limestone base, for all kinds of façades and indoor surfacing.

PROPERTIES

Highly decorative finish. Very easy to apply.

SUPPORT

REVAT CAL ENFOSCADO, REVAT CAL FONDO or **PROPAM REVOC** mortars, traditional mortar renderings, concrete, paint that is in good condition, plaster, plasterboard. The support must be completely set, strong and free from dust and grease.

HOW TO USE

PREPARING THE SUPPORT:

1. The prior rendering can be done with **PROPAM REVOC** or **REVAT CAL BASE**, which provides regular, strong and impermeable support.
2. If applying to smooth concrete, this must be thoroughly free from any remains of release agents.

PREPARING THE MIXTURE:

1. Mix the **REVAT CAL ESTUCO** with 40% clean water (10 liters for every 25 kg bag).
2. Mix manually or mechanically to obtain a even, smooth paste.
3. Leave the already kneaded product to stand for about 5 minutes.
4. Always use the same proportion of water to avoid changes in colour tone.

APPLICATION

1. Spread the mass of **REVAT CAL ESTUCO** in a layer 2 to 4 mm thick, using a trowel.
2. The work joints can be limited with adhesive painting tape.
3. The finish is obtained by floating the applied material with a fine, soft sponge.

PRECAUTIONS

- Do not apply if there is a risk of rain or freezing temperatures.
- Apply at a temperature of between +5°C and +35°C.
- Do not apply to areas immersed in water.
- Protect the lower parts of buildings with base plates.
- During application, protect the areas exposed by rain.
- In exterior applications, it is advisable to perform a protection with **REVAT PROTEC ORG.**

PERFORMANCE

The approximate amount of **REVAT CAL ESTUCO** used is 3 - 4 kg/m².

PACKAGING

25 kg bags.
Colour: Blanco.

STORAGE

In its original closed packaging and protected from damp conditions: 1 year.

SAFETY AND HYGIENE: All the information about conditions of use, storage, transport and removing chemical waste is available on the product Safety Sheet. The product and its packaging must be disposed of according to current legislation and it is the responsibility of the product end user.

LEGAL NOTICE: The data contained in this document is based on our experience and technical knowledge, gained during laboratory assays, and our bibliography. We will not be responsible for any product applications not indicated in this file. The dosing and usage amount data are only guidelines, based on our experience, and may alter due to atmospheric or on-site conditions. For correct dosing and usage amounts, it is necessary to conduct a trial or assay "in situ", for which the client is responsible. If you have any query or require addition information or clarification, please consult our technical department. The valid technical file will always be the latest version uploaded on www.propamsa.es. January 2021.