



REVAT® PLAS

RENDERING ACRYLIC MORTAR FOR FAÇADES

DESCRIPTION

REVAT® PLAS is a render mortar based on acrylic copolymer resins, selected aggregates and additives that provide a protective and decorative building finish.



TECHNICAL DATA

European Technical Approval	ETA 09/0005
Bulk density	1,7 ± 0,1 g/cm³
pH	8,5 ± 0,5%
Dry extract	80 ± 5%
Reaction to fire	Non-inflammable
Application thickness	2 to 3 mm
Application temperature	+5°C to +35°C
Dry to the touch	1 to 3 hours
Content in Volatile Organic Compounds (COV)	≤ 1000 µg/m³

APPLICATIONS

Render for all kinds of façades and interiors on cement mortar renderings, plaster, concrete, etc.

PROPERTIES

Impermeable to rain water.

Breathable.

Excellent adhesion to substrate.

Excellent weather resistance.

SUBSTRATE

Substrate must be completely set, strong and free from dust and grease.

Remove any deteriorated parts, or parts that are in poor condition.

When applied to old coatings, make sure the substrate is in good conditions and well adhered.

HOW TO USE

1. Shake the packaging contents mechanically.
2. When applying with a gun, if necessary, add up to 1 litre (max) of water for each packaging.
3. Apply the material to the substrate with a trowel or gun, depending on the desired finish.
4. Use adhesive painting tape to define working joints.
5. Finally, the material can be floated after 10 to 30 minutes, depending on environmental conditions.

PRECAUTIONS

- Apply to vertical surfaces, or surfaces inclined at least 45°.
- Not applicable to horizontal surfaces exposed to rain water.
- Apply at a temperature of between +5°C and +35°C.
- Do not apply if there is a risk of rain or freezing temperatures.
- Protect the edges against rain water ingress.
- Clean tools immediately with water.
- In case of splashing in the eyes, wash with plenty of water and, if necessary, seek medical advice.

PERFORMANCE

The approximate amount of **REVAT® PLAS** used is 2-3 kg/m².

PACKAGING

20 kg plastic packaging.

Colours: consult colour chart.

STORAGE

In its original closed packaging, in covered areas, protected from heat, humidity and cold (freezing conditions): 2 years.

SAFETY AND HYGIENE: All the information about conditions of use, storage, transport and removing chemical waste is available on the product Safety Sheet. The product and its packaging must be disposed of according to current legislation and it is the responsibility of the product end user.

LEGAL NOTICE: The data contained in this document is based on our experience and technical knowledge, gained during laboratory assays, and our bibliography. We will not be responsible for any product applications not indicated in this file. The dosing and usage amount data are only guidelines, based on our experience, and may alter due to atmospheric or on-site conditions. For correct dosing and usage amounts, it is necessary to conduct a trial or assay "in situ", for which the client is responsible. If you have any query or require additional information or clarification, please consult our technical department. The valid technical file will always be the latest version uploaded on www.propamsa.es. February 2017.