

DECLARATION OF PERFORMANCE – CPR/010.3
European Construction Products Regulation – CPR 305/2011

1. Unique identification code of the product type: **VAT® PORCELÁNICO FLEX**
2. Intended uses: **Cementitious adhesive for ceramic internal and external tiling**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3**
5. Notified body:
LGA Technological Center n°0370 performed the determination of the product type on the basis of type testing on samples taken from the manufacturer, under system 3, and issued the test report 08/32312107
LGA Technological Center n°0370 performed the determination of reaction to fire on the basis of type testing on samples taken from the manufacturer, under system 3, and issued the test report 5016179
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	Class A1	EN 12004:2007 + A1:2012
Bond strength as: - initial tensile adhesion strength	≥ 1 N/mm²	
Durability for: - tensile adhesion strength after water immersion - tensile adhesion strength after heat ageing - tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm² ≥ 1 N/mm² ≥ 1 N/mm²	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 25 of june 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.