

DECLARATION OF PERFORMANCE – CPR/114.2
European Construction Products Regulation – RPC 305/2011


1. Unique identification code of the product type: **PROPAM® FLOOR EPOCEMENT (Before BETOPOX CEMENT)**
2. Intended uses: **Cementitious screed (CT) for use in floor construction internally**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4 and System 3 for Regulation of Reaction to Fire**
5. Notified body:
The manufacturer performed the factory production control (FPC) and initial type testing under system 4 and LGAI Technological Center n°0370 performed the determination of reaction to fire based on type testing on samples taken from the manufacturer, under system 3, and issued the test report 15/9905-324.
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	Class A2 _{FL} s1	EN 13813:2014
Water permeability	NPD	
Water vapour permeability	NPD	
Release of corrosive substances	CT (cement)	
Compressive strength	C40 (≥ 40 N/mm ²)	
Flexural strength	F10 (≥ 10 N/mm ²)	
Wear resistance	A9 (≤ 9 cm ³ / 50 cm ²)	
Impact sound isolation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 08 of august 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.