

PROPAM FLOOR 150 - A

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: PROPAM FLOOR 150 - A

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (): Coating for industrial jointless flooring

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

PROPAMSA SAU
Ctra N-340 Km 1242,3
08620 Sant Vicenç dels Horts - España
Phone: +34 93 680 60 42
constructionsolutions@molins.es
molins.es

1.4 Emergency telephone number: 0034 91 562 04 20

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

This product contains crystalline silica but due to its liquid state it prevents particles within the size range of the breathable fraction from becoming airborne, therefore, the hazard classification linked to it does not apply to the breathable crystalline silica fraction (STOT RE).

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Precautionary statements:

P261: Avoid breathing vapours

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH205: Contains epoxy constituents. May produce an allergic reaction.

Substances that contribute to the classification

benzyl alcohol

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

UFI: 10J0-30XK-500Q-T805

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture composed of additives and epoxy polymers

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: Not relevant	reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)⁽¹⁾ ATP CLP00 Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	25 - <50%
CAS: 14808-60-7 EC: 238-878-4 Index: Not relevant REACH: 01-2120770509-45-XXXX	Quartz (RCS > 10%)⁽¹⁾ Self-classified Regulation 1272/2008 STOT RE 1: H372 - Danger	25 - <50%
CAS: 13462-86-7 EC: 236-664-5 Index: Not relevant REACH: Not relevant	Barite⁽²⁾ Not classified Regulation 1272/2008	2.5 - <10%
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	benzyl alcohol⁽¹⁾ ATP ATP21 Regulation 1272/2008 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Sens. 1B: H317 - Warning	2.5 - <10%
CAS: 28064-14-4 EC: Not relevant Index: Not relevant REACH: Not relevant	Bisphenol F diglycidyl ether resin⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2.5 - <10%
CAS: 2425-79-8 EC: 219-371-7 Index: 603-072-00-7 REACH: 01-2119494060-45-XXXX	1,4-bis(2,3 epoxypropoxy)butane⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2.5 - <10%
CAS: 9003-36-5 EC: 500-006-8 Index: Not relevant REACH: 01-2119454392-40-XXXX	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	<1%
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene⁽²⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	<1%
CAS: 34590-94-8 EC: 252-104-2 Index: Not relevant REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽²⁾ Not classified Regulation 1272/2008	<1%
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	Ethylbenzene⁽²⁾ ATP ATP06 Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	<1%

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Other information:

Identification	Specific concentration limit
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
1,4-bis(2,3 epoxypropoxy)butane CAS: 2425-79-8 EC: 219-371-7	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	11 mg/L	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg	
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	17 mg/L	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	17,2 mg/L	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 5: FIREFIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EEC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 7: HANDLING AND STORAGE (continued)

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 10 °C
Maximum Temp.: 25 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	IOELV (STEL)	
Quartz (RCS > 10%) CAS: 14808-60-7 EC: 238-878-4	IOELV (8h)		0,1 mg/m ³
	IOELV (STEL)		
Barite CAS: 13462-86-7 EC: 236-664-5	IOELV (8h)		0,5 mg/m ³
	IOELV (STEL)		
Xylene ⁽¹⁾ CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
Dipropylene Glycol Methyl Ether ⁽¹⁾ CAS: 34590-94-8 EC: 252-104-2	IOELV (8h)	50 ppm	308 mg/m ³
	IOELV (STEL)		
Ethylbenzene ⁽¹⁾ CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m ³
	IOELV (STEL)	200 ppm	884 mg/m ³

⁽¹⁾ Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0,75 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4,93 mg/m ³	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	40 mg/kg	Not relevant	8 mg/kg	Not relevant
	Inhalation	110 mg/m ³	Not relevant	22 mg/m ³	Not relevant
1,4-bis(2,3 epoxypropoxy)butane CAS: 2425-79-8 EC: 219-371-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	6,66 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4,7 mg/m ³	Not relevant
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 500-006-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	104,15 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	29,39 mg/m ³	Not relevant

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	283 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	308 mg/m ³	Not relevant
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
	Inhalation	Not relevant	293 mg/m ³	77 mg/m ³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	Oral	Not relevant	Not relevant	0,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,0893 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,87 mg/m ³	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Dermal	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Inhalation	27 mg/m ³	Not relevant	5,4 mg/m ³	Not relevant
1,4-bis(2,3 epoxypropoxy)butane CAS: 2425-79-8 EC: 219-371-7	Oral	Not relevant	Not relevant	0,33 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	3,33 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	1,16 mg/m ³	Not relevant
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 500-006-8	Oral	Not relevant	Not relevant	6,25 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	62,5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	8,7 mg/m ³	Not relevant
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Not relevant	Not relevant	36 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	121 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	37,2 mg/m ³	Not relevant
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	1,6 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	15 mg/m ³	Not relevant

PNEC:

Identification					
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L	
	Soil	0,065 mg/kg	Marine water	0,001 mg/L	
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg	
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L	
	Soil	0,456 mg/kg	Marine water	0,1 mg/L	
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,527 mg/kg	
1,4-bis(2,3 epoxypropoxy)butane CAS: 2425-79-8 EC: 219-371-7	STP	100 mg/L	Fresh water	0,024 mg/L	
	Soil	0,003 mg/kg	Marine water	0,002 mg/L	
	Intermittent	0,24 mg/L	Sediment (Fresh water)	0,084 mg/kg	
	Oral	0,000028 g/kg	Sediment (Marine water)	0,008 mg/kg	

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 500-006-8	STP	10 mg/L	Fresh water	0,003 mg/L
	Soil	0,237 mg/kg	Marine water	0 mg/L
	Intermittent	0,025 mg/L	Sediment (Fresh water)	0,294 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,029 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L
	Soil	2,74 mg/kg	Marine water	1,9 mg/L
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Not relevant	Sediment (Marine water)	7,02 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: ABEK)		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN ISO 16321-1:2022 + EN ISO 16321-3:2022 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes		EN ISO 20347:2022/A1:2024	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	1,54 % weight
V.O.C. density at 20 °C:	23,81 kg/m ³ (23,81 g/L)
Average carbon number:	9,71
Average molecular weight:	141,59 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	148,14 kg/m ³ (148,14 g/L)
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Dense
Colour:	Tintometric system
Odour:	Soft
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	216 °C
Vapour pressure at 20 °C:	57 Pa
Vapour pressure at 50 °C:	348,68 Pa (0,35 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1546 kg/m ³
Relative density at 20 °C:	1,546
Dynamic viscosity at 20 °C:	2000 - 3000 mPa·s
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	260 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Distillates (petroleum), hydrotreated light (3: Not classifiable as to its carcinogenicity to humans); Ethylbenzene (2B: Possibly carcinogenic to humans); Xylene (3: Not classifiable as to its carcinogenicity to humans); Quartz (RCS > 10%) (1: Carcinogenic to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Contains substances that have been listed by the International Agency for Research on Cancer (IARC) as Group 1 human carcinogens. However, exposure to such substances does not occur during normal use of products in which the substance is bound to other materials, such as rubber, inks, paints, etc., in a liquid state or polymer-encapsulated.

Specific toxicology information on the substances:

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
1,4-bis(2,3 epoxypropoxy)butane CAS: 2425-79-8 EC: 219-371-7	LD50 oral	3609 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	11 mg/L	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg	
	LD50 dermal		
	LC50 inhalation vapour		
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	17 mg/L	Rat
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation vapour		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation vapour	17,2 mg/L	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
Bisphenol F diglycidyl ether resin CAS: 28064-14-4 EC: Not relevant	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol CAS: 9003-36-5 EC: 500-006-8	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50 10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50 1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Not relevant		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50 42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50 75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 63 mg/L (3 h)	Chlorella vulgaris	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	NOEC Not relevant		
	NOEC 0,3 mg/L	Daphnia magna	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC 1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1,17 mg/L	Ceriodaphnia dubia	Crustacean

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC	Not relevant		
	NOEC	0,5 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Not relevant		
	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	0 %
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	94 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BOD5	Not relevant	Concentration	Not relevant
	COD	0 g O ₂ /g	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	73 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	BCF	4
	Pow Log	2.8
	Potential	Low
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	1
	Pow Log	1.05
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	15.7	Henry	8,8E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Special regulations: 274, 335, 375, 601, 650
Tunnel restriction code: -
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
Special regulations: 375, 335, 274, 969
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
- 14.3 Transport hazard class(es):** 9
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: *benzyl alcohol (100-51-6) - PT: (6)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200,000	500,000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:

- CONTINUED ON NEXT PAGE -

PROPAM FLOOR 150 - A

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Substances that contribute to the classification (SECTION 2):

- Removed substances
 - reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)
 - Bisphenol F diglycidyl ether resin (28064-14-4)
 - 1,4-bis(2,3 epoxypropoxy)butane (2425-79-8)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H411: Toxic to aquatic life with long lasting effects.
H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1B: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Classification procedure:

Skin Irrit. 2: Calculation method
Skin Sens. 1B: Calculation method
Aquatic Chronic 2: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

** Changes with regards to the previous version

PROPAM FLOOR 150 - A

SECTION 16: OTHER INFORMATION ** (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -