

DECLARATION OF PERFORMANCE – CPR/102.2

European Construction Products Regulation – CPR 305/2011

1. Name of the product: **LEAKINJECT 2K FLEX**
2. Type of product: **Concrete injection product for ductile filling of cracks (D)**
3. Intended uses: **In buildings and civil engineering works**
4. Name and contact address of the manufacturer:
PROPAMSA S.A.U.
Camí Ciments Molins, s/n. 08620 Sant Vicenç dels Horts
www.propamsa.es
5. System of assessment and verification of constancy of performance: **System 2+**
6. Notified laboratory:
BCCA Belgian Construction Certification Association nº0749 performed the evaluation of the factory production control (FPC) under system 2+ and issued the test certificate BC2/565-1895-0004-001
7. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Adhesion and elongation capacity	$\geq 1,3 \text{ N/mm}^2$ (on dry concrete) $\geq 0,6 \text{ N/mm}^2$ (on wet concrete) $\geq 3,5 \text{ N/mm}^2$ (on sand-blasted metal sheet) $> 10 \%$ (Elongation)	EN 1504-5:2004
Impermeability to water	$\geq 2 \cdot 10^5 \text{ Pa}$	
Glass transition temperature	$\geq 40^\circ\text{C}$	
Workability - Crack width - Moisture state of the crack	$> 0,1 \text{ mm}$ Dry, damp and wet	
Durability (Concrete compatibility)	Lost of deformation work $< 20\%$	
Corrosion behaviour	NPD	
Release of dangerous substances	Compliance with 5.4 See SDS	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, 01/12/2016

All the information on conditions of use, employment and storage should be consulted in the product datasheet.