



**PROPAM FLOOR 150 TIX - A**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** PROPAM FLOOR 150 TIX - A  
**Other means of identification:**  
**UFI:** 3XH0-M085-V006-4WE3
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses (Professional users): Coating for industrial jointless flooring  
Relevant uses (Industrial user): Coating for industrial jointless flooring  
For Professional users/Industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
PROPAMSA SAU  
Ctra N-340 Km 1242,3  
08620 Sant Vicenç dels Horts - España  
Phone: +34 93 680 60 42  
constructionsolutions@molins.es  
molins.es
- 1.4 Emergency telephone number:** 0034 91 562 04 20

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Acute Tox. 4: Acute toxicity, Category 4, H302+H332  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Warning**
- 

- Hazard statements:**  
Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Precautionary statements:**  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Supplementary information:**  
EUH205: Contains epoxy constituents. May produce an allergic reaction.
- Substances that contribute to the classification**  
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700); benzyl alcohol; Bisphenol F diglycidyl ether resin; 1,4-bis(2,3 epoxypropoxy)butane
- UFI:** 3XH0-M085-V006-4WE3

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Not relevant

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives and epoxy polymers

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification  | Chemical name/Classification   | Concentration         |
|---|--|-----------------------|
| CAS: 25068-38-6<br>EC: 500-033-5<br>Index: 603-074-00-8<br>REACH: Not relevant            | <b>reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight <math>\leq</math> 700)<sup>(1)</sup></b> ATP CLP00 | <b>50 - &lt;75 %</b>  |
|   | Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning                                |                       |
| CAS: 100-51-6<br>EC: 202-859-9<br>Index: 603-057-00-5<br>REACH: 01-2119492630-38-XXXX     | <b>benzyl alcohol<sup>(1)</sup></b> Self-classified  | <b>10 - &lt;25 %</b>  |
|   | Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319 - Warning   |                       |
| CAS: 28064-14-4<br>EC: Not relevant<br>Index: Not relevant<br>REACH: Not relevant         | <b>Bisphenol F diglycidyl ether resin<sup>(1)</sup></b> Self-classified  | <b>2,5 - &lt;10 %</b> |
|   | Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning                                |                       |
| CAS: 2425-79-8<br>EC: 219-371-7<br>Index: 603-072-00-7<br>REACH: 01-2119494060-45-XXXX    | <b>1,4-bis(2,3 epoxypropoxy)butane<sup>(1)</sup></b> ATP CLP00   | <b>2,5 - &lt;10 %</b> |
|   | Regulation 1272/2008 Acute Tox. 4: H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning                                |                       |
| CAS: Not relevant<br>EC: 905-588-0<br>Index: Not relevant<br>REACH: 01-2119539452-40-XXXX | <b>Reaction mass of ethylbenzene and xylene<sup>(1)</sup></b> Self-classified  | <b>1 - &lt;2,5 %</b>  |
|   | Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning  |                       |
| CAS: 34590-94-8<br>EC: 252-104-2<br>Index: Not relevant<br>REACH: 01-2119450011-60-XXXX   | <b>Dipropylene Glycol Methyl Ether<sup>(2)</sup></b> Not classified  | <b>&lt;1 %</b>        |
|   | Regulation 1272/2008   |                       |

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

| Identification   | Specific concentration limit  |
|--|---|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | % (w/w) $\geq$ 5: Skin Irrit. 2 - H315<br>% (w/w) $\geq$ 5: Eye Irrit. 2 - H319 |

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification   | Acute toxicity         | Genus         |
|--|------------------------|---------------|
| 1,4-bis(2,3 epoxypropoxy)butane<br>CAS: 2425-79-8<br>EC: 219-371-7 | LD50 oral              | Not relevant  |
|  | LD50 dermal            | 1100 mg/kg    |
|  | LC50 inhalation vapour | 11 mg/L       |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9                   | LD50 oral              | 500 mg/kg     |
|  | LD50 dermal            | Not relevant  |
|  | LC50 inhalation vapour | 15,192 mg/L * |

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

| Identification   | Acute toxicity         |              | Genus |
|--|------------------------|--------------|-------|
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0 | LD50 oral              | 3523 mg/kg   | Rat   |
|  | LD50 dermal            | Not relevant |       |
|  | LC50 inhalation vapour | 11 mg/L      |       |

\* Equivalent ATE value of the substance applicable to the exposure route of the product. For the ATE value associated with the exposure route of the substance, see section 11.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

Non-applicable

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 5: FIREFIGHTING MEASURES (continued)**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 7: HANDLING AND STORAGE (continued)**

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification                                 | Occupational exposure limits |         |                       |
|--|------------------------------|---------|-----------------------|
| Reaction mass of ethylbenzene and xylene       | IOELV (8h)                   | 50 ppm  | 221 mg/m <sup>3</sup> |
| CAS: Not relevant EC: 905-588-0                | IOELV (STEL)                 | 100 ppm | 442 mg/m <sup>3</sup> |
| Dipropylene Glycol Methyl Ether <sup>(1)</sup> | IOELV (8h)                   | 50 ppm  | 308 mg/m <sup>3</sup> |
| CAS: 34590-94-8 EC: 252-104-2                  | IOELV (STEL)                 |         |                       |

<sup>(1)</sup> Skin

**DNEL (Workers):**

| Identification   |            | Short exposure        |                       | Long exposure          |                       |
|--|------------|-----------------------|-----------------------|------------------------|-----------------------|
|  |            | Systemic              | Local                 | Systemic               | Local                 |
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | Oral       | Not relevant          | Not relevant          | Not relevant           | Not relevant          |
|  | Dermal     | Not relevant          | Not relevant          | 0,75 mg/kg             | Not relevant          |
|  | Inhalation | Not relevant          | Not relevant          | 4,93 mg/m <sup>3</sup> | Not relevant          |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9   | Oral       | Not relevant          | Not relevant          | Not relevant           | Not relevant          |
|  | Dermal     | 40 mg/kg              | Not relevant          | 8 mg/kg                | Not relevant          |
|  | Inhalation | 110 mg/m <sup>3</sup> | Not relevant          | 22 mg/m <sup>3</sup>   | Not relevant          |
| 1,4-bis(2,3 epoxypropoxy)butane<br>CAS: 2425-79-8<br>EC: 219-371-7   | Oral       | Not relevant          | Not relevant          | Not relevant           | Not relevant          |
|  | Dermal     | Not relevant          | Not relevant          | 6,66 mg/kg             | Not relevant          |
|  | Inhalation | Not relevant          | Not relevant          | 4,7 mg/m <sup>3</sup>  | Not relevant          |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0   | Oral       | Not relevant          | Not relevant          | Not relevant           | Not relevant          |
|  | Dermal     | Not relevant          | Not relevant          | 212 mg/kg              | Not relevant          |
|  | Inhalation | 442 mg/m <sup>3</sup> | 442 mg/m <sup>3</sup> | 221 mg/m <sup>3</sup>  | 221 mg/m <sup>3</sup> |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2  | Oral       | Not relevant          | Not relevant          | Not relevant           | Not relevant          |
|  | Dermal     | Not relevant          | Not relevant          | 283 mg/kg              | Not relevant          |
|  | Inhalation | Not relevant          | Not relevant          | 308 mg/m <sup>3</sup>  | Not relevant          |

**DNEL (General population):**

| Identification   |            | Short exposure       |              | Long exposure          |              |
|--|------------|----------------------|--------------|------------------------|--------------|
|  |            | Systemic             | Local        | Systemic               | Local        |
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | Oral       | Not relevant         | Not relevant | 0,5 mg/kg              | Not relevant |
|  | Dermal     | Not relevant         | Not relevant | 0,0893 mg/kg           | Not relevant |
|  | Inhalation | Not relevant         | Not relevant | 0,87 mg/m <sup>3</sup> | Not relevant |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9   | Oral       | 20 mg/kg             | Not relevant | 4 mg/kg                | Not relevant |
|  | Dermal     | 20 mg/kg             | Not relevant | 4 mg/kg                | Not relevant |
|  | Inhalation | 27 mg/m <sup>3</sup> | Not relevant | 5,4 mg/m <sup>3</sup>  | Not relevant |
| 1,4-bis(2,3 epoxypropoxy)butane<br>CAS: 2425-79-8<br>EC: 219-371-7   | Oral       | Not relevant         | Not relevant | 0,33 mg/kg             | Not relevant |
|  | Dermal     | Not relevant         | Not relevant | 3,33 mg/kg             | Not relevant |
|  | Inhalation | Not relevant         | Not relevant | 1,16 mg/m <sup>3</sup> | Not relevant |

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification   |            | Short exposure        |                       | Long exposure          |                        |
|--|------------|-----------------------|-----------------------|------------------------|------------------------|
|  |            | Systemic              | Local                 | Systemic               | Local                  |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0 | Oral       | Not relevant          | Not relevant          | 12,5 mg/kg             | Not relevant           |
|  | Dermal     | Not relevant          | Not relevant          | 125 mg/kg              | Not relevant           |
|  | Inhalation | 260 mg/m <sup>3</sup> | 260 mg/m <sup>3</sup> | 65,3 mg/m <sup>3</sup> | 65,3 mg/m <sup>3</sup> |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2            | Oral       | Not relevant          | Not relevant          | 36 mg/kg               | Not relevant           |
|  | Dermal     | Not relevant          | Not relevant          | 121 mg/kg              | Not relevant           |
|  | Inhalation | Not relevant          | Not relevant          | 37,2 mg/m <sup>3</sup> | Not relevant           |

**PNEC:**

| Identification   |              |               |                         |             |  |
|--|--------------|---------------|-------------------------|-------------|--|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | STP          | 10 mg/L       | Fresh water             | 0,006 mg/L  |  |
|  | Soil         | 0,065 mg/kg   | Marine water            | 0,001 mg/L  |  |
|  | Intermittent | 0,018 mg/L    | Sediment (Fresh water)  | 0,341 mg/kg |  |
|  | Oral         | 0,011 g/kg    | Sediment (Marine water) | 0,034 mg/kg |  |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9   | STP          | 39 mg/L       | Fresh water             | 1 mg/L      |  |
|  | Soil         | 0,456 mg/kg   | Marine water            | 0,1 mg/L    |  |
|  | Intermittent | 2,3 mg/L      | Sediment (Fresh water)  | 5,27 mg/kg  |  |
|  | Oral         | Not relevant  | Sediment (Marine water) | 0,527 mg/kg |  |
| 1,4-bis(2,3 epoxypropoxy)butane<br>CAS: 2425-79-8<br>EC: 219-371-7   | STP          | 100 mg/L      | Fresh water             | 0,024 mg/L  |  |
|  | Soil         | 0,003 mg/kg   | Marine water            | 0,002 mg/L  |  |
|  | Intermittent | 0,24 mg/L     | Sediment (Fresh water)  | 0,084 mg/kg |  |
|  | Oral         | 0,000028 g/kg | Sediment (Marine water) | 0,008 mg/kg |  |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0   | STP          | 6,58 mg/L     | Fresh water             | 0,327 mg/L  |  |
|  | Soil         | 2,31 mg/kg    | Marine water            | 0,327 mg/L  |  |
|  | Intermittent | 0,327 mg/L    | Sediment (Fresh water)  | 12,46 mg/kg |  |
|  | Oral         | Not relevant  | Sediment (Marine water) | 12,46 mg/kg |  |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2  | STP          | 4168 mg/L     | Fresh water             | 19 mg/L     |  |
|  | Soil         | 2,74 mg/kg    | Marine water            | 1,9 mg/L    |  |
|  | Intermittent | 190 mg/L      | Sediment (Fresh water)  | 70,2 mg/kg  |  |
|  | Oral         | Not relevant  | Sediment (Marine water) | 7,02 mg/kg  |  |

**8.2 Exposure controls:**



**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

| Pictogram   | PPE  | Labelling   | CEN Standard        | Remarks  |
|---|--|---|---------------------|--|
| <br>Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

**C.- Specific protection for the hands**

| Pictogram  | PPE                                   | Labelling   | CEN Standard | Remarks  |
|--|---------------------------------------|---|--------------|--|
| <br>Mandatory hand protection | Protective gloves against minor risks |  |              | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018 |



As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**



- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



| Pictogram  | PPE   | Labelling   | CEN Standard                    | Remarks   |
|--|---|---|---------------------------------|---|
| <br>Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

**E.- Body protection**

| Pictogram | PPE                  | Labelling   | CEN Standard      | Remarks   |
|-----------|----------------------|---|-------------------|---|
|           | Work clothing        |  |                   | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
|           | Anti-slip work shoes |  | EN ISO 20347:2022 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019                                 |

**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure  | Standards                                       | Emergency measure   | Standards                                      |
|--|---|---|--|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

|                           |                                     |
|---------------------------|-------------------------------------|
| V.O.C. (Supply):          | 3,64 % weight                       |
| V.O.C. density at 20 °C:  | 40,02 kg/m <sup>3</sup> (40,02 g/L) |
| Average carbon number:    | 7,13                                |
| Average molecular weight: | 103,48 g/mol                        |

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| V.O.C. density at 20 °C:             | 152,57 kg/m <sup>3</sup> (152,57 g/L) |
| EU limit for the product (Cat. A.J): | 500 g/L (2010)                        |
| Components:                          | Not relevant                          |

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

|                          |                |
|--------------------------|----------------|
| Physical state at 20 °C: | Liquid         |
| Appearance:              | Translucent    |
| Colour:                  | Colourless     |
| Odour:                   | Not relevant * |
| Odour threshold:         | Not relevant * |

**Volatility:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**PROPAM FLOOR 150 TIX - A**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

|  |                        |
|--|------------------------|
| Boiling point at atmospheric pressure:       | 199 °C                 |
| Vapour pressure at 20 °C:                    | 893 Pa                 |
| Vapour pressure at 50 °C:                    | 4279,98 Pa (4,28 kPa)  |
| Evaporation rate at 20 °C:                   | Not relevant *         |
| <b>Product description:</b>                  |                        |
| Density at 20 °C:                            | 1100 kg/m <sup>3</sup> |
| Relative density at 20 °C:                   | 1,109                  |
| Dynamic viscosity at 20 °C:                  | 750 - 1250 mPa·s       |
| Kinematic viscosity at 20 °C:                | Not relevant *         |
| Kinematic viscosity at 40 °C:                | Not relevant *         |
| Concentration:                               | Not relevant *         |
| pH:  | Not relevant *         |
| Vapour density at 20 °C:                     | Not relevant *         |
| Partition coefficient n-octanol/water 20 °C: | Not relevant *         |
| Solubility in water at 20 °C:                | Not relevant *         |
| Solubility properties:                       | Not relevant *         |
| Decomposition temperature:                   | Not relevant *         |
| Melting point/freezing point:                | Not relevant *         |
| <b>Flammability:</b>                         |                        |
| Flash Point:                                 | Non Flammable (>60 °C) |
| Flammability (solid, gas):                   | Not relevant *         |
| Autoignition temperature:                    | 260 °C                 |
| Lower flammability limit:                    | Not relevant *         |
| Upper flammability limit:                    | Not relevant *         |
| <b>Particle characteristics:</b>             |                        |
| Median equivalent diameter:                  | Not relevant *         |

**9.2 Other information:**

**Information with regard to physical hazard classes:**

|  |                |
|--|----------------|
| Explosive properties:  | Not relevant * |
| Oxidising properties:  | Not relevant * |
| Corrosive to metals:   | Not relevant * |
| Heat of combustion:  | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |

**Other safety characteristics:**

|                           |                |
|---------------------------|----------------|
| Surface tension at 20 °C: | Not relevant * |
| Refraction index:         | Not relevant * |

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

- CONTINUED ON NEXT PAGE -



**PROPAM FLOOR 150 TIX - A**

**SECTION 10: STABILITY AND REACTIVITY (continued)**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight   | Humidity       |
|--------------------|------------------|-------------------------|------------|----------------|
| Not applicable     | Not applicable   | Precaution              | Precaution | Not applicable |

**10.5 Incompatible materials:**

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

**10.6 Hazardous decomposition products:**

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Distillates (petroleum), hydrotreated light (3); ethanol (1); Reaction mass of ethylbenzene and xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

| Identification   | Acute toxicity         |             | Genus  |
|--|------------------------|-------------|--------|
| 1,4-bis(2,3 epoxypropoxy)butane<br>CAS: 2425-79-8<br>EC: 219-371-7             | LD50 oral              | 3609 mg/kg  | Rat    |
|  | LD50 dermal            | 1100 mg/kg  |        |
|  | LC50 inhalation gases  | 4500 mg/L   |        |
|  | LC50 inhalation vapour | 11 mg/L     |        |
|  | LC50 inhalation dust   | 1,5 mg/L    |        |
|  | LC50 inhalation mist   | 1,5 mg/L    |        |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9                               | LD50 oral              | 500 mg/kg   | Rat    |
|  | LD50 dermal            | 2500 mg/kg  |        |
|  | LC50 inhalation mist   | 3,3 mg/L    | Rat    |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0 | LD50 oral              | 3523 mg/kg  | Rat    |
|  | LD50 dermal            | >5000 mg/kg | Rat    |
|  | LC50 inhalation gases  | 4500 mg/L   |        |
|  | LC50 inhalation vapour | 11 mg/L     |        |
|  | LC50 inhalation dust   | 1,5 mg/L    |        |
|  | LC50 inhalation mist   | 1,5 mg/L    |        |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2            | LD50 oral              | >5000 mg/kg | Rat    |
|  | LD50 dermal            | 9510 mg/kg  | Rabbit |
|  | LC50 inhalation        |             |        |

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

**12.1 Toxicity:**

**Acute toxicity:**

| Identification   | Concentration            | Species                 | Genus      |
|--|--------------------------|-------------------------|------------|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | LC50 >1 - 10 mg/L (96 h) |                         | Fish       |
|  | EC50 >1 - 10 mg/L (48 h) |                         | Crustacean |
|  | EC50 >1 - 10 mg/L (72 h) |                         | Algae      |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9   | LC50 646 mg/L (48 h)     | Leuciscus idus          | Fish       |
|  | EC50 400 mg/L (24 h)     | Daphnia magna           | Crustacean |
|  | EC50 79 mg/L (3 h)       | Scenedesmus subspicatus | Algae      |

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

| Identification  | Concentration  | Species                              | Genus                       |
|---|--|--------------------------------------|-----------------------------|
| Bisphenol F diglycidyl ether resin<br>CAS: 28064-14-4<br>EC: Not relevant | LC50 >1 - 10 mg/L (96 h)<br>EC50 >1 - 10 mg/L (48 h)<br>EC50 >1 - 10 mg/L (72 h) |                                      | Fish<br>Crustacean<br>Algae |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2       | LC50 10000 mg/L (96 h)<br>EC50 1919 mg/L (48 h)<br>EC50 Not relevant             | Pimephales promelas<br>Daphnia magna | Fish<br>Crustacean          |

**Chronic toxicity:**

| Identification  | Concentration                      | Species                                   | Genus              |
|---|------------------------------------|---|--------------------|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6 EC: 500-033-5 | NOEC Not relevant<br>NOEC 0,3 mg/L |   |                    |
| benzyl alcohol<br>CAS: 100-51-6 EC: 202-859-9   | NOEC 48,897 mg/L<br>NOEC 51 mg/L   | N/A<br>Daphnia magna                      | Fish<br>Crustacean |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant EC: 905-588-0   | NOEC 1,3 mg/L<br>NOEC 1,17 mg/L    | Oncorhynchus mykiss<br>Ceriodaphnia dubia | Fish<br>Crustacean |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8 EC: 252-104-2  | NOEC Not relevant<br>NOEC 0,5 mg/L |   |                    |

**12.2 Persistence and degradability:**

**Substance-specific information:**

| Identification   | Degradability  | Biodegradability   |
|--|--|--|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin<br>(number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | BOD5 Not relevant<br>COD Not relevant<br>BOD5/COD Not relevant | Concentration 100 mg/L<br>Period 28 days<br>% Biodegradable 0 %      |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9   | BOD5 Not relevant<br>COD Not relevant<br>BOD5/COD Not relevant | Concentration 100 mg/L<br>Period 14 days<br>% Biodegradable 94 %     |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2  | BOD5 Not relevant<br>COD 0 g O2/g<br>BOD5/COD Not relevant     | Concentration Not relevant<br>Period 28 days<br>% Biodegradable 73 % |

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

| Identification  | Bioaccumulation potential               |
|---|---|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)<br>CAS: 25068-38-6<br>EC: 500-033-5 | BCF 4<br>Pow Log 2.8<br>Potential Low   |
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9  | BCF 0<br>Pow Log 1.1<br>Potential Low   |
| Reaction mass of ethylbenzene and xylene<br>CAS: Not relevant<br>EC: 905-588-0  | BCF 9<br>Pow Log 2.77<br>Potential Low  |
| Dipropylene Glycol Methyl Ether<br>CAS: 34590-94-8<br>EC: 252-104-2   | BCF 1<br>Pow Log -0.06<br>Potential Low |

**12.4 Mobility in soil:**

| Identification                                   | Absorption/desorption   | Volatility   |
|--|---|--|
| benzyl alcohol<br>CAS: 100-51-6<br>EC: 202-859-9 | Koc Not relevant<br>Conclusion Not relevant<br>Surface tension 3,679E-2 N/m (25 °C) | Henry Not relevant<br>Dry soil Not relevant<br>Moist soil Not relevant |

**12.5 Results of PBT and vPvB assessment:**

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description  | Waste class (Regulation (EU) No 1357/2014) |
|-----------|--|--|
| 08 04 09* | waste adhesives and sealants containing organic solvents or other hazardous substances | Hazardous                                  |

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



**14.1 UN number or ID number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))

**14.3 Transport hazard class(es):** 9

Labels: 9

**14.4 Packing group:** III

**14.5 Environmental hazards:** Yes

**14.6 Special precautions for user**

Special regulations: 274, 335, 375, 601

Tunnel restriction code: -

Physico-Chemical properties: see section 9

Limited quantities: 5 L

**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 41-22:

**PROPAM FLOOR 150 TIX - A**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN3082  
**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))  
**14.3 Transport hazard class(es):** 9  
**Labels:** 9  
**14.4 Packing group:** III  
**14.5 Marine pollutant:** Yes  
**14.6 Special precautions for user**  
Special regulations: 335, 969, 274  
EmS Codes: F-A, S-F  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not relevant  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN3082  
**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))  
**14.3 Transport hazard class(es):** 9  
**Labels:** 9  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
Physico-Chemical properties: see section 9  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: *benzyl alcohol (100-51-6) - PT: (6)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

**Seveso III:**

| Section | Description           | Lower-tier requirements | Upper-tier requirements |
|---------|-----------------------|-------------------------|-------------------------|
| E2      | ENVIRONMENTAL HAZARDS | 200                     | 500                     |

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

**SECTION 15: REGULATORY INFORMATION (continued)**

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Not relevant

**Texts of the legislative phrases mentioned in section 2:**

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H302+H332: Harmful if swallowed or if inhaled.

H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

**Classification procedure:**

Skin Irrit. 2: Calculation method

Skin Sens. 1: Calculation method

Aquatic Chronic 2: Calculation method

Acute Tox. 4: Calculation method

Eye Irrit. 2: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

- CONTINUED ON NEXT PAGE -

**PROPAM FLOOR 150 TIX - A**

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -