

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)
- Other means of identification:**  
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses (): Two component high performance coating for metallic surfaces, wood, concrete, etc...  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
PROPAMSA SAU  
Ctra N-340 Km 1242,3  
08620 Sant Vicenç dels Horts - España  
Phone: +34 93 680 60 42  
constructionsolutions@molins.es  
molins.es
- 1.4 Emergency telephone number:** 0034 91 562 04 20

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Muta. 2: Germ cell mutagenicity, Category 2, H341  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Warning**
- 
- Hazard statements:**  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Muta. 2: H341 - Suspected of causing genetic defects.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Precautionary statements:**  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a poison center/doctor.  
P312: Call a POISON CENTER/doctor if you feel unwell.  
P337+P313: If eye irritation persists: Get medical advice/attention.  
P352: Wash with plenty of water.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P391: Collect spillage.  
P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.
- Supplementary information:**  
EUH205: Contains epoxy constituents. May produce an allergic reaction.
- UFI:** 2DPS-H7D4-KWNM-WAC4

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Not relevant

**3.2 Mixture:**

**Chemical description:** Mixture composed of epoxy resin in solvents

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: Not relevant	<b>reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight <math>\leq</math> 700)<sup>(1)</sup></b> ATP CLP00 Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	<b>75 - &lt;100%</b>
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	<b>benzyl alcohol<sup>(1)</sup></b> ATP ATP21 Regulation 1272/2008 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Sens. 1B: H317 - Warning	<b>10 - &lt;25%</b>
CAS: 26761-45-5 EC: 247-979-2 Index: 607-770-00-2 REACH: 01-2119431597-33-XXXX	<b>2,3-epoxypropyl neodecanoate<sup>(1)</sup></b> ATP ATP22 Regulation 1272/2008 Muta. 2: H341; Skin Sens. 1A: H317 - Warning	<b>2.5 - &lt;10%</b>

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700) CAS: 25068-38-6 EC: 500-033-5	% (w/w) $\geq$ 5: Skin Irrit. 2 - H315 % (w/w) $\geq$ 5: Eye Irrit. 2 - H319
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	% (w/w) $\geq$ 0,001: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity	Genus
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg
	LD50 dermal	Not relevant
	LC50 inhalation vapour	Not relevant

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

**By skin contact:**

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 4: FIRST AID MEASURES (continued)**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

Non-applicable

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EEC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 10 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0,75 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4,93 mg/m <sup>3</sup>	Not relevant

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	40 mg/kg	Not relevant	8 mg/kg	Not relevant
	Inhalation	110 mg/m <sup>3</sup>	Not relevant	22 mg/m <sup>3</sup>	Not relevant
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	4,2 mg/kg	Not relevant
	Inhalation	11,76 mg/m <sup>3</sup>	Not relevant	5,88 mg/m <sup>3</sup>	Not relevant

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	Oral	Not relevant	Not relevant	0,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,0893 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,87 mg/m <sup>3</sup>	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Dermal	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Inhalation	27 mg/m <sup>3</sup>	Not relevant	5,4 mg/m <sup>3</sup>	Not relevant
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	2,5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4 mg/m <sup>3</sup>	Not relevant

**PNEC:**

Identification				
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L
	Soil	0,065 mg/kg	Marine water	0,001 mg/L
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L
	Soil	0,456 mg/kg	Marine water	0,1 mg/L
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,527 mg/kg
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	STP	50 mg/L	Fresh water	0,001 mg/L
	Soil	Not relevant	Marine water	0,00012 mg/L
	Intermittent	0,012 mg/L	Sediment (Fresh water)	0,012 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,002 mg/kg

**8.2 Exposure controls:**

**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN ISO 16321-1:2022 + EN ISO 16321-3:2022 EN ISO 18526-(1,2,3,4):2020 EN ISO 18526-(1,2,3,4):2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 EN ISO 18526-(1,2,3,4):2020 EN ISO 13982-1:2004/A1:2010 ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2022 EN 13832-1:2018	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,5 % weight
V.O.C. density at 20 °C:	5,6 kg/m <sup>3</sup> (5,6 g/L)
Average carbon number:	9,55
Average molecular weight:	172,26 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	5,64 kg/m <sup>3</sup> (5,64 g/L)
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Not relevant

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Not relevant *
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not relevant *

**Volatility:**

Boiling point at atmospheric pressure:	205 °C
Vapour pressure at 20 °C:	15 Pa
Vapour pressure at 50 °C:	77,04 Pa (0,08 kPa)
Evaporation rate at 20 °C:	Not relevant *

**Product description:**

Density at 20 °C:	1128 kg/m <sup>3</sup>
Relative density at 20 °C:	1,129
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

**Flammability:**

Flash Point:	99 °C (Pensky-Martins (CC))
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	450 °C
Lower flammability limit:	1,3 % Volume
Upper flammability limit:	12,9 % Volume

**Particle characteristics:**

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

**Other safety characteristics:**

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Not relevant
- Mutagenicity: Exposure to this product can cause genetic modifications. For more specific information on the possible health effects see section 2.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	LD50 oral	970000 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg	
	LD50 dermal		
	LC50 inhalation vapour		

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	LC50	5 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	4,8 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	3 mg/L (72 h)	Selenastrum capricornutum	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CAS: 25068-38-6 EC: 500-033-5	NOEC	Not relevant		
	NOEC	0,3 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700) CAS: 25068-38-6 EC: 500-033-5	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	0 %
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	94 %
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	BOD5	Not relevant	Concentration	3 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	7 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
	Parameter	Value
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700) CAS: 25068-38-6 EC: 500-033-5	BCF	4
	Pow Log	2.8
	Potential	Low
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	1
	Pow Log	1.05
	Potential	Low
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	BCF	371
	Pow Log	4.4
	Potential	High

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	15.7	Henry	8,8E-2 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Yes
2,3-epoxypropyl neodecanoate CAS: 26761-45-5 EC: 247-979-2	Koc	143	Henry	Not relevant
	Conclusion	High	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP11 Mutagenic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated  
Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Special regulations: 274, 335, 375, 601, 650  
Tunnel restriction code: -  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 42-24:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**  
Special regulations: 375, 335, 274, 969  
EmS Codes: F-A, S-F  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2026:

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A  
(Before BETOPOX PRIMER A)**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN3082  
**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700))  
**14.3 Transport hazard class(es):** 9  
 Labels: 9  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: *benzyl alcohol (100-51-6) - PT: (6)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200,000	500,000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Not relevant

**Texts of the legislative phrases mentioned in section 2:**

- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H317: May cause an allergic skin reaction.
- H341: Suspected of causing genetic defects.
- H411: Toxic to aquatic life with long lasting effects.

- CONTINUED ON NEXT PAGE -

**PROPAM PRIMER EPO A**  
**(Before BETOPOX PRIMER A)**

**SECTION 16: OTHER INFORMATION (continued)**

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H302 - Harmful if swallowed.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Muta. 2: H341 - Suspected of causing genetic defects.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Skin Sens. 1A: H317 - May cause an allergic skin reaction.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.

**Classification procedure:**

Skin Irrit. 2: Calculation method  
Eye Irrit. 2: Calculation method  
Skin Sens. 1: Calculation method  
Muta. 2: Calculation method  
Aquatic Chronic 2: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -