

DECLARATION OF PERFORMANCE – CPR/043.4
European Construction Products Regulation – CPR 305/2011

1. Unique identification code of the product type: **PROPAM® IMPE FLEX**
2. Intended uses: **Liquid applied water impermeable cementitious mortar modified with polymers (CM) for all external applications and swimming pools beneath ceramic tiles**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4, System 3 for watertightness**
5. Notified body:
LGAI Technological Center n°0370 performed the determination of the product type on the basis of type testing on samples taken from the manufacturer, under system 3, and issued the test report 23/32304948M1
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Water tightness Resistance to crack propagation (-5°C) Bond strength as: - initial tensile adhesion strength	Without penetration ≥ 0,75 mm ≥ 0,5 N/mm ²	EN 14891:2017
Durability for: - tensile adhesion strength after water immersion - tensile adhesion strength after heat ageing - tensile adhesion strength after freeze-thaw cycles - tensile adhesion strength after limewater immersion - tensile adhesion strength after chlorinated water immersion	≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ²	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 27 of July 2026

All the information on conditions of use, employment and storage should be consulted in the product data sheet.

N.I.F. A58580234 | Registro Mercantil de Barcelona, Hoja B-2605 | Sociedad Unipersonal

