

DECLARATION OF PERFORMANCE – CPR/071.3
European Construction Products Regulation – CPR 305/2011

1. Unique identification code of the product type: **PROPAM® GROUT 102 CABLE (Before CABLEGROUT)**
2. Intended uses: **Cementitious mortar for concrete injection with transmission of forces (F). Anchoring cementitious mortar for strengthening concrete by installing reinforcing steel (rebars) in buildings and civil engineering works**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4**
5. Notified body:
The manufacturer performed the factory production control (FPC) and initial type testing under system 4
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Adhesion by tensile bond strength	> 2 N/mm ²	EN 1504-5:2004
Exudation	≤ 1 %	
Change in volume	Between 1% and 5% of the initial volume	
Chloride ion content	< 0,2%	
Workability - Crack width - Moisture state of the crack	> 0,5 mm Dry and damp	
Flow time	180 s	
Workability period	75 min	
Setting time	Initial: 360 min	
Adhesion by tensile bond strength after thermal dry-wet cycles	>70% of the value of adhesion by tensile bond strength	
Concrete compatibility	>70% of the value of adhesion by tensile bond strength	
Release of dangerous substances	Compliance with 5.4 See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 17 of July 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.