

DECLARATION OF PERFORMANCE – CPR/116.2
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM® WALL FINO PLUS (Before PROPAM FINO PLUS)**
2. Intended uses: **General purpose rendering/plastering mortar (GP) for use in walls, ceilings, columns and partitions covered by the scope of EN 998-1 standard**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4**
5. Notified body:
The manufacturer performed the factory production control (FPC) and initial type testing under system 4
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	Class A1	EN 998-1:2010
Capillary water absorption	W2($\leq 0,2 \text{ kg/m}^2 \cdot \text{min}^{0,5}$)	
Water vapour permeability coefficient (μ)	≤ 15	
Adhesion	$\geq 0,3 \text{ N/mm}^2$ (Tipo B)	
Thermal conductivity (λ_{10} , dry)	$0,70 \pm 0,05 \text{ W/m}\cdot\text{K}$	
Compressive strength	CS III (3,5 – 7,5 N/mm^2)	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 08 of august 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.