

DECLARATION OF PERFORMANCE – CPR/188.2
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM® FLOOR 150 COND**
2. Intended uses: **Mortar for screeds and floor finishes based on synthetic resin for use on interior floors in construction**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4 and System 3 for Fire Reaction Regulation**
5. Notified body:
The manufacturer has carried out the factory production control (CPF) and the initial type tests under system 4, while LGAI Technological Center n°0370 has carried out the determination of the reaction to fire based on the tests carried out on samples taken from the manufacturer, under system 3, and issued in report 24/32300058
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	B _{fi} S1	EN 13813:2002
Release of corrosive substances	SR (Resina Sintética)	
Water permeability	PND	
Wear resistance	AR0,5 (≤50µm)	
Bond strength	B2,0 (≥ 2 N/mm ²)	
Impact resistance	IR14,7 (≥ 14,7Nm)	
Electrical resistance	ER10 ⁴ (1x10 ⁴ Ω)	
Surface hardness	SH30(≥ 30 N/mm ²)	
Acoustic insulation	PND	
Acoustic absorption	PND	
Thermal resistance	PND	
Chemical resistance	PND	
Release of dangerous substances	See SDS	

Performances determined in the Propam Floor Multilayer Quartz Color Conductive system

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 08 of august 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.