

DECLARATION OF PERFORMANCE – CPR/192.2
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM FLOOR 170 COND**
2. Intended uses: **Mortar for screeds and floor finishes based on synthetic resin for use on interior floors in construction**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 4 and System 3 for Fire Reaction Regulation**
5. Notified body:
The manufacturer has carried out the factory production control (CPF) and the initial type tests under system 4, while LGAI Technological Center n°0370 has carried out the determination of the reaction to fire based on the tests carried out on samples taken from the manufacturer, under system 3, and issued in report 24/32300063
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	B _{FLS1}	EN 13813:2002
Release of corrosive substances	SR (Synthetic Resin)	
Water permeability	NPD	
Wear resistance	AR0,5 ($\leq 50 \mu\text{m}$)	
Tensile strength	B2,0 ($\geq 2 \text{ N/mm}^2$)	
Impact resistance	IR14,7 ($\geq 14,7 \text{ Nm}$)	
Surface hardness	SH100 ($\geq 100 \text{ N/mm}^2$)	
Compressive strength	C30 ($\geq 30 \text{ N/mm}^2$)	
Flexural strength	F30 ($\geq 30 \text{ N/mm}^2$)	
Electrical resistance	ER10 ⁴ ($1 \times 10^4 \Omega$)	
Acoustic insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 08 of august 2024

All the information on conditions of use, employment and storage should be consulted in the product data sheet.