

DECLARATION OF PERFORMANCE – CPR/203.1
European Construction Products Regulation – RPC 305/2011


1. Unique identification code of the product type: **PROPAM® SEAL MS30**
2. Intended uses:
 - Sealant for façade joints in interior and exterior applications EN 15651-1:2012: Type F – EXT-INT-CC, class 20LM.
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3, System 4 (for reaction to fire)**
5. Notified body:
FUNDACION TECNALIA RESEARCH & INNOVATION, (notified body nº 1292), has carried out initial type tests and issued a test report
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN-13501-1:2007+A1 2010)	Class F	EN 15651-1:2012
Resistance to Flow (EN ISO 7390)	≤ 3 mm	
Loss of volumen (EN ISO 10563)	≤ 10 %	
Adhesion / cohesion with extension maintained afterwards of immersion in water (EN ISO 10590)	Pass	
Tensile properties (drying modulus at 23°C) (EN ISO 8339)	≥ 0.4 MPa	
Tensile properties (secant modulus at -30°C) (EN ISO 8339)	≤ 0.9 MPa	
Tensile properties with maintained extension (EN ISO 8340)	Pass	
Durability	Pass	
Emission of substances dangerous to the environment or health	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 31 of July 2025

All the information on conditions of use, employment and storage should be consulted in the product data sheet.