

DECLARATION OF PERFORMANCE – CPR/205.1
European Construction Products Regulation – RPC 305/2011


1. Unique identification code of the product type: **PROPAM SEAL AC40 F**
2. Intended uses: **Sealant for joints on facades for interior and exterior applications. EN 15651-1:2017: Type F – EXT-INT, Class 12.5P**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3**
5. Notified body:
FUNDACION TECNALIA RESEARCH & INNOVATION, (notified body no. 1292), has carried out initial type tests and issued a test report
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN-13501-1:2007+A1 2010)	Class B	EN 15651-1:2017
Emission of hazardous substances into the environment or to human health	See FDS	
Air and water tightness		
Creep resistance (EN ISO 7390)	≤ 3 mm	
Volume loss (EN ISO 10563)	≤ 25 %	
Tensile properties (deformation) after immersion in water at 23°C (plastic) (EN ISO 10591)	≥ 100%	
Tensile properties (elongation at break) at 23°C (EN ISO 8339)	≥ 25%	EN 15651-1:2012
Adhesion/cohesion with sustained extension after immersion in water (EN ISO 10590)	Pass	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 11 of november 2025

All the information on conditions of use, employment and storage should be consulted in the product data sheet.