

DECLARATION OF PERFORMANCE – CPR/207.1
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM SEAL SN30**
2. Intended uses:
 - Sealant for joints on facades in interior and exterior applications. EN 15651-1:2012: Type F - EXT-INT, class 25LM
 - Sealant for glazing applications. EN 15651-2:2012: Type G, class 25LM
 - Sealant for sanitary joints: EN 15651-3; type S, class S1
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3**
5. Notified body:
FUNDACION TECNALIA RESEARCH & INNOVATION, (notified body no. 1292), has carried out initial type tests and issued a test report
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN-13501-1:2007+A1 2010)	Class F	EN 15651-1,-2,-3:2012
Emission of hazardous substances into the environment or to human health	See FDS	
Air and water tightness		
Creep resistance (EN ISO 7390)	≤ 3 mm	EN 15651-1,-2,-3 :2012
Volume loss (EN ISO 10563)	≤ 40 %	EN 15651-1,-2,-3 :2012
Elastic recovery (EN ISO 7389)	≥ 60%	EN 15651-2
Deformation properties after immersion in water (EN ISO 10591)	≥ 25%	EN 15651-1,-3 :2012
Adhesion/cohesion after exposure to heat, water, and artificial light (EN ISO 11431)	Pass	EN 15651-2
Tensile properties (secant modulus at 23°C) (EN ISO 8339)	≤ 0.4 MPa	EN 15651-1,-2 :2012
Tensile properties with sustained extension (EN ISO 8340)	Pass	EN 15651-1,-2 :2012
Action by microorganisms (EN ISO 846)	1	EN 15651-3
Durability	Pass	EN 15651-1,-2,-3 :2012

- Conditioning: Method A
- Substrates: Glass, anodized aluminum and M2 concrete, without primer.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 20 of november 2025

All the information on conditions of use, employment and storage should be consulted in the product data sheet.