

DECLARATION OF PERFORMANCE – CPR/208.1
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM SEAL SN30 F**
2. Intended uses: **Mastic d'étanchéité pour joints de façades, pour applications intérieures et extérieures. EN 15651-1:2012 : Type F – EXT-INT-CC, classe 25HM**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3**
5. Notified body:
FUNDACION TECNALIA RESEARCH & INNOVATION, (notified body no. 1292), has carried out initial type tests and issued a test report
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN-13501-1:2007+A1 2010)	Class B	EN 15651-1:2012
Emission of hazardous substances into the environment or to human health	See FDS	
Air and water tightness		
Creep resistance (EN ISO 7390)	≤ 3 mm	
Volume loss (EN ISO 10563)	≤ 10 %	
Adhesion/cohesion with sustained extension after immersion in water (EN ISO 10590)	Pass	
Tensile properties (secant modulus at 23°C) (EN ISO 8339)	≥ 0.4 MPa	
Tensile properties with sustained extension (EN ISO 8340)	Pass	
Durability	Pass	

- Conditioning: Method A
- Substrates: M2 Concrete

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oscar Grau Fuentes
Technical Director




Sant Vicenç dels Horts, the 20 of november 2025

All the information on conditions of use, employment and storage should be consulted in the product data sheet.