

DECLARATION OF PERFORMANCE – CPR/216.1
European Construction Products Regulation – RPC 305/2011

1. Unique identification code of the product type: **PROPAM® AISTERM PLACA FIBRA MADERA**
2. Intended uses: **Thermal insulation products for buildings – factory-made wood fiber (WF) products.**
3. Manufacturer:
PROPAMSA S.A.U.
Ctra N-340 Km 1242.3
08620 Sant Vicenç dels Horts – España
molins.es
4. System of assessment and verification of constancy of performance (AVCP): **System 3**
5. Notified body:
Otto-Graf-Institut Universität Stuttgart Forschungs- und Materialprüfungsanstalt (MPA) Pfaffenwaldring 4 D-70569 Stuttgart, notified body no. 0672
6. Declared performance:

Essential Characteristic	Performance	Harmonised technical specification
Reaction to fire	Reaction to fire	E
Release of dangerous substances	Release of dangerous substances	NPD
Sound absorption	Sound absorption	NPD
Sound absorption (for Flooring)	Dynamic stiffness	NPD
	Thickness dL	NPD
	Compressibility	NPD
	Air flow resistance	AFr100
Mouldering performance	Mouldering	NPD
Thermal resistance	Thermal resistance and thermal conductivity	$\lambda d = 0.039 \text{ W/mK}$
	Thickness	T5 / See label
Short term water absorption	Water absorption	WS1.0
Water vapour transmission	Water vapour transmission	MU3
Compressive strength	Compressive strength	CS(10Y)50
	Point load	NPD
Durability of the reaction to fire under the influence of heat, weather conditions and aging	Reaction to fire	NPD
Durability of the thermal resistance and thermal conductivity under the influence of heat, weather conditions and aging	Thermal resistance and thermal conductivity	NPD
	Dimensional stability	NPD
	Dimensional stability at 70°C	DS(70.-)2

EN 13171:2012 +
A1:2015

	Dimensional stability at specified temperature and humidity	NPD	
Tensile strength	Tensile strength parallel to faces	NPD	
	Tensile strength vertical to faces	TR7.5	
Durability of the compressive strength under the influence of aging	Long term compressive creep	NPD	

NPD: No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Oscar Grau Fuentes
Technical Director



Sant Vicenç dels Horts, the 24 of february 2026

All the information on conditions of use, employment and storage should be consulted in the product data sheet.